

AVANT

Ceiling cord mounted • Dry location listed

Specifications:

Description:

A modern LED pendant featuring contrasting textures including sandblasted glass inside accented by a polished outside surface. 3000K, 623 lumens, 90+CRI. Energy Star.

Construction:

- Brushed Nickel (-09) (plated)
- Steel construction
- Glass: Clear Outside Sandblase Inside glass shade
- LED Module is replaceable (Part # 93054049)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- CA Title 24 compliant
- Canopy covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied

Performance:

Number of Modules	1
Input Power	9W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30
Max. Operating Temp	30
Warranty	5 year warranty
Labels	cCSAus Dry location listed ENERGY STAR® qualified

Catalog number:

Base	Finish	Color Temp	CRI
P5072	09 - Brushed Nickel	30K - 3000K	9 - 90 CRI

P5072-0930K9

Images:



Dimensions:

Diameter: 9"
Height: 4-3/4"
Overall ht. w/cord: 125"

Glass: 9" dia.



AVANT

Ceiling cord mounted • Dry location listed



P5072-0930K9

Dimming Notes:

P5072 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300P)
--------	-------------	--------------------------

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.