

CORNICE

Wall mount • Wet location listed



Specifications:

Description:

Modern geometric outdoor LED sconces are designed to complement a range of residential and commercial architectural styles. ADA compliant. 9w LED is 3000K, 90+ CRI in a Metallic Gray cast aluminum shade. Dark Sky compliant.

Construction:

Metallic Gray (-82) (powdercoat)
 Cast aluminum construction

LED Module is replaceable (part # 93054049)
 Flicker-free dimming to 10% brightness with most ELV type dimmers
 (See Dimming Notes)
 Title 24 compliant
 Unit covers a standard 4" hexagonal recessed outlet box
 Mounting strap for outlet box included
 Six inches of wire supplied

Performance:

Number of Modules	1
Input Power	9W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000K
CRI	90+
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Wet location listed ENERGY STAR® qualified

P5635-8230K9

Images:



Dimensions:

Width: 6-1/8"
 Height: 5"
 Depth: 4"
 H/CTR: 2-3/8"

Catalog number:

Base	Finish	Color Temp	CRI
P5635	82 - Metallic Gray	30K - 3000K	9 - 90 CRI