

LED SQ CYLINDER

Wall mounted • Damp location listed



Specifications:

Description:

6" LED Square Cylinder Up/Down Wall lantern

Construction:

White (-30)
Die-cast aluminum construction

Flicker-free dimming to 10% brightness with most ELV type dimmers
(See Dimming Notes)
Backplate covers a standard 4" hexagonal recessed outlet box
4-1/2" sq. Mounting strap for outlet box included
6" of wire supplied
White finish
Powder coat for chipping and fading resistance
Heavy-duty construction
Wet location listed when used with P8797 top cover lens (sold separately).

Performance:

Number of Modules	2
Input Power	29W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	2000/68 (LM-79) per module
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cULus Damp location listed

P5644-30-30K

Images:



Dimensions:

Width: 6"
Height: 18

Catalog number:

Base
P5644

Finish
30 - White

Color Temp
30K - 3000K

CRI
Blank- 90 CRI

LED SQ CYLINDER

Wall mounted • Damp location listed



P5644-30-30K

Dimming Notes:

P5644 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300P)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.