

# VALERA LED

Wall mounted • Wet location listed



## Specifications:

### Description:

Clean lines are up front and center for these modern LED outdoor sconces. Valera features a die-cast aluminum frame and matte white, acrylic diffuser. Energy efficient LED source offers 3000K color temperature and 90+CRI output. Title 24 compliant. Two-light 9w LED wall lantern in a Brushed Nickel finish.

### Construction:

Brushed Nickel (-09) (plated)  
 Steel construction  
 Glass: Polycarbonate acrylic diffuser  
 LED Module is replaceable (part # 93054049) Flicker-free dimming to 10% brightness with most ELV type dimmers  
 (See Dimming Notes)  
 Title 24 compliant  
 Chassis covers a standard 4" hexagonal recessed outlet box  
 Mounting strap for outlet box included  
 6" of wire supplied  
 Modern LED outdoor sconce  
 Clean lines are central to design  
 Features a die-cast aluminum frame and matte white, acrylic diffuser

### Performance:

|                     |                                |
|---------------------|--------------------------------|
| Number of Modules   | 2                              |
| Input Power         | 9W                             |
| Input Voltage       | 120V                           |
| Input Frequency     | 60Hz                           |
| Lumens/LPW          | 623/69.2 (LM-79) per module    |
| CCT                 | 3000K                          |
| CRI                 | 90+                            |
| Life                | 60,000 (L70/TM-21)             |
| EMI/RFI             | FCC Title 47, Part 15, Class B |
| Min. Start Temp     | -30° C                         |
| Max. Operating Temp | 30° C                          |
| Warranty            | 5 year warranty                |
| Labels              | cCSAus Wet location listed     |
|                     | ENERGY STAR® qualified         |

**P5806-0930K9**

### Images:



### Dimensions:

Width: 5-5/8"  
 Height: 16"  
 Depth: 4"  
 H/CTR: 8"

### Catalog number:

| Base         | Finish                     | Color Temp         | CRI               |
|--------------|----------------------------|--------------------|-------------------|
| <b>P5806</b> | <b>09 - Brushed Nickel</b> | <b>30K - 3000K</b> | <b>9 - 90 CRI</b> |

# VALERA LED

Wall mounted • Wet location listed



## P5806-0930K9

### Dimming Notes:

P5806 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

#### Electronic Low Voltage ELV Reverse Phase Controls

|         |               |                          |
|---------|---------------|--------------------------|
| Lutron  | Diva Series   | (Part Number DVELV-300P) |
| Lutron  | Nova T Series | (Part Number NTELV-300)  |
| Lutron  | Vierti Series | (Part Number VTELV-600)  |
| Lutron  |               | (Part Number MAELV-600)  |
| Lutron  |               | (Part Number SPELV-600)  |
| Leviton |               | (Part Number AWRMG-EAW)  |
| Leviton |               | (Part Number 6615-P)     |

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.