

P7253 LED

Ceiling mounted • Damp location listed



Description:

Close-to-ceiling, surface mount round with clean modern lines and white acrylic diffuser. DC LED light engine with 1184 delivered lumens at 3000K and 90+ CRI.

Specifications:

Brushed Nickel (-09) (plated)
Steel construction
White acrylic diffuser
Dimmable (See Dimming Notes)
Unit covers a standard 4" hexagonal recessed outlet box
Mounting strap for outlet box included
6" of wire supplied
ENERGY STAR® qualified

Performance:

Input Power	22w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens	1184
CCT	3000 K
CRI	90
Life (hours)	54,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30°C
Warranty	5 year warranty
Labels	cULus Damp location listed
	ENERGY STAR® qualified

P7253-0930K9

Images:



Dimensions:

Diameter: 14"
Height: 3-3/4"

P7253 LED

Ceiling mounted • Damp location listed



Photometrics:

P7253-0930K9

ELECTRICAL DATA P7253-0930K9

Input Voltage	120 V
Input Frequency	60 Hz
Input Current	0.183 A
Input Power	22
Power Factor	>0.90
THD	<20%
EMI Filtering	FCC 47CFR Part 15, Class B
Operating Temperature	-30 °C to 30°C
Dimming	Yes*

Over-voltage, over-current, short-circuit protected

*See Dimming Notes for more information

P7253-0930K9


LED Light Engine: 3000 K 90 CRI

System Wattage: 22

Fixture delivered lumens: 1184

Fixture Efficacy: 53.8

Spacing Criteria: 1.0



ZONAL LUMEN SUMMARY

ZONE	LUMENS	%LUMINAIRE
0-30	238	20.1
0-40	395	33.4
0-60	724	61.1
0-90	1037	87.6
90-120	103	8.7
90-130	122	10.3
90-150	143	12.1
90-180	147	12.4
0-180	1184	100

P7253-0930K9

Dimming Notes:

P7253-0930K9 is designed to be compatible with many Forward and Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron NTEVL-300

Lutron DVELV-300P

Lutron DVCL-253P

Lutron Caseta Wireless

Leviton 6681

Leviton 6672

Leviton 6674

Lutron AYLTV-600P

Lutron NTLV-600

Lutron MAELV-601

Leviton AWRMG-EAW

Lutron N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.