
4 IN. SQUARE WELDED BOXES - 2-1/8 IN. DEEP WITH CONDUIT KO'S

4 in. Square Boxes, 2-1/8 in. Deep - Welded with Conduit KO's 600V

A13





Catalog #: 232RAC

APPLICATIONS

RACO® Boxes are installed in walls or ceilings for lighting fixtures, switches or receptacles

Square boxes are used where multiple conductor runs are split into two or more directions to bring power to a number of electrical devices

PRODUCT FEATURES

Combination screw heads provide for faster installation

TKO® Knockouts offer greater flexibility with RACO patented combination 1/2" and 3/4" knockout N/A

UL LISTED

File F195978

COMPLIANCES

All RACO® single gang, two gang, 4 in. square, and single gang gangable UL listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult UL "Fire Resistance Directory" or the UL website at www.ul.com 600V Per UL 514-A, suitable for use without a bonding jumper in circuits up to 600 volts

FIRE RESISTANCE

Acceptable for use in 2-hour rated walls

GENERAL PRODUCT INFORMATION

Wiring System: Conduit Country of Origin: USA

CONFIGURATION

Bracket Type: Drawn or Welded: No Bracket Welded Raised Ground: No

Side Knockout(s): (8) 1/2 in. & (4) TKO® (3) 1/2 in. & (2) TKO® Bottom Knockouts(s)

DRAWING DIMENSIONS

Dimension A: 2-1/8 in.

PRODUCT MEASUREMENTS

Depth: 2-1/8 in Cubic Inches (cm3): 30.3 (496.5) Wt. Ea. (Lbs.): Product Length (in.): 0.898 2.19 Product Width (in.): Product Height (in.): 4.00

PACKAGING

Minimum Pack Qty.: Std. Pkg.: 25 25 Product UPC-A Labeled: No Weight (Lbs. Per/C): Ship Carton Length (in.): 89 80 18.75 Ship Carton Width (in.): Ship Carton Height (in.): 8.88 7.38 Ctn Weight (Lbs.): 22.45 Pallet Qty: 1750 UPC Number: 050169602324 12of5 50050169602329

Page 1 / 1