




COLOR-CODED STRAIGHT STRAIN RELIEF CONDUIT AND CORD CONNECTORS

Color-Coded Straight Strain Relief Cord Connectors Steel
N/A

B58.1



Catalog #: 3725-1

APPLICATIONS

For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable
RACO liquidtight strain relief cord connectors are suitable for use in Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 hazardous locations

PRODUCT FEATURES

Neoprene grommets are color-coded by cable diameter allowing for quick and easy identification
Steel construction provides mechanical strength and durability
Metallic components are zinc plated for corrosion protection
Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened creating a liquidtight seal
Time saving and easy installation - no need to disassemble the fitting for cord installation
Male tapered thread NPT
Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
N/A

CULUS

UL File E195973

NEMA

NEMA 4

GENERAL PRODUCT INFORMATION

Trade Size: 1-1/4 in.
Cable Range: .85 - .95
Color Code: Gray

DRAWING DIMENSIONS

Dimension A: 1.94
Dimension B: 1.88

PACKAGING

Package Type: Carton
Ship Carton Qty.: 25
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 44.90
Ship Carton Length (in.): 6.00
Ship Carton Width (in.): 6.00
Ship Carton Height (in.): 6.00
Ctn Weight (Lbs.): 11.23
UPC Number: 050169983157
I2of5: 50050169983152