# COLOR-CODED STRAIGHT STRAIN RELIEF CONDUIT AND CORD CONNECTORS

## Color-Coded Straight Strain Relief Cord Connectors Steel

N/A

B58.1

Table

| RACO NO. | TRADE SIZE | COLOR CODE | CABLE RANGE | DIM A | DIM B |
|---|---|---|---|---|---|
| 3720-5 | 1/2" | RED | 150-260 | 1.44 | 1.13 |
| 3720-1 | 1/2" | WHITE | 250-350 | 1.44 | 1.13 |
| 3720-2 | 1/2" | BLUE | 350-450 | 1.44 | 1.13 |
| 3720-3 | 1/2" | GREEN | 450-560 | 1.44 | 1.13 |
| 3720-4 | 1/2" | YELLOW | 550-750 | 1.44 | 1.13 |
| 3723-5 | 3/4" | RED | 150-250 | 1.60 | 1.25 |
| 3723-1 | 3/4" | WHITE | 250-350 | 1.60 | 1.25 |
| 3723-2 | 3/4" | BLUE | 350-450 | 1.60 | 1.25 |
| 3723-3 | 3/4" | GREEN | 450-560 | 1.60 | 1.25 |
| 3723-4 | 3/4" | YELLOW | 550-750 | 1.60 | 1.25 |
| 3723-6 | 3/4" | YELLOW | 650-750 | 1.60 | 1.31 |
| 3723-5 | 3/4" | PURPLE | 750-850 | 1.60 | 1.31 |
| 3724-6 | 1" | GREEN | 450-560 | 1.75 | 1.50 |
| 3724-1 | 1" | BROWN | 550-650 | 1.75 | 1.50 |
| 3724-4 | 1" | YELLOW | 650-750 | 1.75 | 1.50 |
| 3724-5 | 1" | PURPLE | 750-850 | 1.75 | 1.50 |
| 3724-3 | 1" | GRAY | 850-950 | 1.94 | 1.63 |
| 3724-2 | 1" | BLACK | 850-1.050 | 1.94 | 1.63 |
| 3726-5 | 1-1/4" | PURPLE | 750-850 | 194 | 1.88 |
| 3726-1 | 1-1/4" | GRAY | 850-950 | 1.94 | 1.88 |
| 3726-2 | 1-1/4" | BLACK | 850-1.050 | 1.94 | 1.88 |
| 3726-4 | 1-1/4" | ORANGE | 1.050-1.150 | 2.06 | 2.00 |
| 3726-3 | 1-1/4" | RED | 1.150-1.250 | 2.06 | 2.00 |
| 3726-7 | 1-1/4" | WHITE | 1.250-1.375 | 2.06 | 2.00 |
| 3726-6 | 1-1/2" | BLACK | 850-1.050 | 2.13 | 2.25 |
| 3726-1 | 1-1/2" | ORANGE | 1.050-1.150 | 2.13 | 2.25 |
| 3726-2 | 1-1/2" | RED | 1.150-1.250 | 2.13 | 2.25 |
| 3726-3 | 1-1/2" | WHITE | 1.250-1.375 | 2.13 | 2.25 |







**Catalog #**: 3726-1

### APPLICATIONS

For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable
RACO liquidtight strain relief cord connectors are suitable for use in Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 hazardous locations

### PRODUCT FEATURES

Neoprene grommets are color-coded by cable diameter allowing for quick and easy identification
Steel construction provides mechanical strength and durability
Metallic components are zinc plated for corrosion protection
Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened creating a liquidtight seal
Time saving and easy installation - no need to disassemble the fitting for cord installation
Male tapered thread NPT
Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
N/A

### CULUS

UL File E195973

### NEMA

NEMA 4

### GENERAL PRODUCT INFORMATION

| | |
|---|---|
| Trade Size: | 1-1/2 in. |
| Cable Range: | 1.05 - 1.15 |
| Color Code: | Orange |

### DRAWING DIMENSIONS

| | |
|---|---|
| Dimension A: | 2.13 |
| Dimension B: | 2.25 |

### PACKAGING

| | |
|---|---|
| Package Type: | Carton |
| Ship Carton Qty.: | 25 |
| Product UPC-A Labeled: | No |
| Weight (Lbs. Per/C): | 69.80 |
| Ship Carton Length (in.): | 9.00 |
| Ship Carton Width (in.): | 7.00 |
| Ship Carton Height (in.): | 5.00 |
| Ctn Weight (Lbs.): | 17.45 |
| UPC Number: | 050169983218 |
| I2of5: | 50050169983213 |