




## COLOR-CODED 90° STRAIN RELIEF CONDUIT AND CORD CONNECTORS

Color-Coded 90° Strain Relief Cord Connectors Malleable Iron  
N/A

B58.2



| Table    |            |            |             |       |      |
|----------|------------|------------|-------------|-------|------|
| RACO NO. | TRADE SIZE | COLOR CODE | CABLE RANGE | USM A | DM B |
| 3794-9   | 1/2"       | RED        | 150-200     | 2.75  | 1.25 |
| 3794-3   | 1/2"       | WHITE      | 200-300     | 2.75  | 1.25 |
| 3794-2   | 1/2"       | BLUE       | 300-400     | 2.75  | 1.25 |
| 3794-4   | 1/2"       | GREEN      | 400-500     | 2.75  | 1.25 |
| 3794-5   | 1/2"       | BROWN      | 500-600     | 2.75  | 1.25 |
| 3795-9   | 3/4"       | RED        | 150-200     | 3.25  | 1.44 |
| 3795-3   | 3/4"       | WHITE      | 200-300     | 3.25  | 1.44 |
| 3795-2   | 3/4"       | BLUE       | 300-400     | 3.25  | 1.44 |
| 3795-4   | 3/4"       | GREEN      | 400-500     | 3.25  | 1.44 |
| 3795-5   | 3/4"       | BROWN      | 500-600     | 3.25  | 1.44 |
| 3795-6   | 1"         | GREEN      | 600-700     | 3.25  | 1.75 |
| 3795-7   | 1"         | PURPLE     | 700-800     | 3.25  | 1.44 |
| 3795-1   | 1"         | BROWN      | 800-900     | 3.75  | 1.75 |
| 3795-8   | 1"         | YELLOW     | 900-1000    | 3.75  | 1.75 |
| 3795-4   | 1"         | GRAY       | 200-300     | 3.88  | 1.75 |
| 3795-5   | 1"         | BLACK      | 300-400     | 3.88  | 1.75 |



Catalog #: 3794-1

## APPLICATIONS

For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable  
RACO liquidtight strain relief cord connectors are suitable for use in Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 hazardous locations

## PRODUCT FEATURES

Neoprene grommets are color-coded by cable diameter allowing for quick and easy identification  
Malleable Iron construction provides mechanical strength and durability  
Metallic components are zinc plated for corrosion protection  
Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened creating a liquidtight seal  
Time saving and easy installation - no need to disassemble the fitting for cord installation  
Male tapered thread NPT  
Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel  
N/A

## CULUS

UL File E195973

## NEMA

NEMA 4

## GENERAL PRODUCT INFORMATION

Trade Size: 1/2 in.  
Cable Range: .25 - .35  
Color Code: White

## DRAWING DIMENSIONS

Dimension A: 2.75  
Dimension B: 1.25

## PACKAGING

Package Type: Carton  
Ship Carton Qty.: 25  
Product UPC-A Labeled: No  
Weight (Lbs. Per/C): 29.60  
Ship Carton Length (in.): 6.00  
Ship Carton Width (in.): 6.00  
Ship Carton Height (in.): 4.00  
Ctn Weight (Lbs.): 7.40  
UPC Number: 050169983256  
I2of5: 50050169983251