

Threaded/Set Screw Fittings: T Body Only
1-1/2" Combo T Type Body

C13.1



TABLE 1

TRACE SIZE	CATHODE NUMBER	A	B	C	D	E	F	G TAPPED HOLES
1.52	CT130	8.90	3.30	1.52	7.24	2.54	3.30	#2.53X2.53
1.27		8.90	3.30	1.27	7.24	2.54	3.30	#2.53X2.53

FIGURE 1

The diagram illustrates the dimensions and parameters of a wire mesh structure. Key dimensions and parameters are labeled as follows:

- WIRE THICKNESS:** 0.305, 0.381, 1.127 IN (7.62, 9.65, 28.58 mm)
- VOLUME:** 361.57 IN³ (5.92 L)
- MONITOR WIRE FIL:** #2 AWG MAX
- SECTION (S4):** #12.5X12.5X3 #2.53X2.53
- MAXIMUM WIRE FILL:** Indicated by a green arrow pointing to the wire mesh.
- CATHODE SPACING:** 3.30 IN (83.82 mm)
- VOLUME:** 361.57 IN³ (5.92 L)
- WIRE MESH (X):** Indicated by a green arrow pointing to the wire mesh.
- WIRE MESH THROAT (X):** Indicated by a green arrow pointing to the throat of the wire mesh.
- WIRE MESH THROAT (X):** Indicated by a green arrow pointing to the throat of the wire mesh.

APPLICATIONS

For use with threaded rigid/IMC conduit, or EMT, for pulling access or to split a run into multiple directions.
N/A

PRODUCT FEATURES

Durable die cast aluminum construction
Premium powder coat finish
Combination head screw

CULUS

Listed

NEMA

NEMA 3R Rated

NEC

2014 NEC Compliant

GENERAL PRODUCT INFORMATION

Trade Size:	1-1/2"
Description Table:	1-1/2" Combo T Type Body

PACKAGING

Package Type:	Carton
Std. Pkg.:	2
Ship Carton Qty.:	10
Product UPC-A Labeled:	Yes
Weight (Lbs. Per/C):	87
Ship Carton Length (in.):	21.65
Ship Carton Width (in.):	7.09
Ship Carton Height (in.):	9.65
Ctn Weight (Lbs.):	11.02
Pallet Qty:	480
UPC Number:	050169815588
I2of5:	05050169815583