


4 IN. SQUARE WELDED BOXES - 2-1/8 IN. DEEP WITH ARMORED CABLE / METAL CLAD / FLEX CLAMPS

4 in. Square Welded Boxes - 2-1/8 in. Deep with Armored Cable / Metal Clad / Flex Clamps
4 Square Box 2-1/8 in. Deep w/STAB-ITs on top CM
600V, 8" #12 Solid Copper Pigtail

A18



Catalog #: 244SCM

APPLICATIONS

RACO® STAB-IT boxes are great for any job where flexible armored cable is being used
RACO® Boxes are installed in walls or ceilings for lighting fixtures, switches or receptacles

PRODUCT FEATURES

Designed for quick installation of flex, MC, MCI, MCI-A, AC, and HCF Cable
TKO® Knockouts offer greater flexibility with RACO patented combination 1/2 in. and 3/4 in. knockout

UL LISTED

File E195978

COMPLIANCES

All RACO® single gang, two gang, 4 in. square, and single gang UL listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult UL "Fire Resistance Directory" or the UL website at www.ul.com
600V Per UL 514-A, suitable for use without a bonding jumper in circuits up to 600 volts
MSDS
www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_Steel_Boxes_and_Covers.pdf

FIRE RESISTANCE

Acceptable for use in 2-hour rated walls

GENERAL PRODUCT INFORMATION

Wiring System:	Armored Cable/Metal Clad/MCI-A/Flex
Country of Origin:	China

CONFIGURATION

Cable Priouts:	4
Bracket Type:	No Bracket
Drawn or Welded:	Welded
Raised Ground:	Yes
Side Knockout(s):	(4) 1/2 in., (2) 1/2 in. - 3/4 in. TKO
Bottom Knockouts(s):	(1) 1/2 in., (1) 1/2 in. - 3/4 in. TKO

PRODUCT MEASUREMENTS

Depth:	2-1/8 in.
Cubic Inches (cm3):	30.3 (496.5)
Wt. Ea. (Lbs.):	1.231
Product Length (in.):	2.430
Product Width (in.):	4.00
Product Height (in.):	4.15

PACKAGING

Minimum Pack Qty.:	25
Std. Pkg.:	25
Product UPC-A Labeled:	No
Weight (Lbs. Per/C):	123.136
Ship Carton Length (in.):	18.750
Ship Carton Width (in.):	7.375
Ship Carton Height (in.):	8.500
Ctn Weight (Lbs.):	30.784
Pallet Qty:	1750
UPC Number:	050169962442
I2of5:	50050169962447