




RIGID BODIES AND ASSEMBLIES

T Assembly
N/A

C13



Part Number	A	B	C	D	E	F	G	H	Material	Finish	Weight (lbs.)	Volume (in³)
RLT350	16.30	7.66	5.59	5.55	13.687	3-1/2	3-1/2	3.538	Aluminum	Powder Coat	8.50	318.3



Catalog #: RLT350

APPLICATIONS

For use with threaded rigid/IMC conduit for pulling access or to split a run into multiple directions. Removable cover allows access for maintenance and making taps and splices to conductors.
N/A

PRODUCT FEATURES

- Durable die cast aluminum construction
- Premium powder coat finish
- Includes NBR synthetic rubber gasket
- Stamped aluminum cover
- Combination head screw

UL LISTED

File E331564

NEMA

NEMA 3R rated

NEC

2014 NEC® compliant

GENERAL PRODUCT INFORMATION

Trade Size: 3-1/2 in.

DRAWING DIMENSIONS

Dimension A: 16.30 in.
Dimension B: 7.66 in.
Dimension C: 5.59 in.
Dimension D: 5.55 in.
Dimension E: 13.687 in.
Dimension F: Tapped holes #5/16UNC-2B
Dimension G: 3-1/2-8NPT
Dimension H: 3.538 in.

PRODUCT MEASUREMENTS

Cubic Inches (cm³): 318.3 (5215)

PACKAGING

Package Type: Carton
Ship Carton Qty.: 1
Product UPC-A Labeled: Yes
Weight (Lbs. Per/C): 850.00
Ship Carton Length (in.): 17.00
Ship Carton Width (in.): 7.63
Ship Carton Height (in.): 7.00
Ctn Weight (Lbs.): 8.50
UPC Number: 092326213486
I2of5: 30092326213487