


PS 655, PS 656, PS 901, PS 902, PS 930, PS 2580, PS 2585 – Raceway End Caps



Part No.	Use With	Finish	A	Wt./100 pcs
PS 902	PS 100	EG, DF	3/4"	22
PS 2580	PS 150	EG	27/16"	18
PS 655	PS 200	EG, DF	1 5/8"	11
PS 2585	PS 210	EG	1 5/8"	12
PS 656	PS 300	EG	1 3/8"	15
PS 901	PS 400	EG	1"	11
PS 930	PS 500	EG, DF	1 3/16"	5

MATERIAL:

All Power-Strut fittings are formed in punch press dies from mild, pickled and oiled, bar or strip steel. Plain or electro-galvanized fittings meet the requirements for ASTM A575 and A-576, or ASTM A-36.

STANDARD DIMENSIONS:

Standard dimensions on all fittings are as follows except where otherwise indicated:

- Fitting Thickness: 1/4"
- Fitting Width: 15/8"
- Hole Diameter: 9/16"
- Hole Spacing: 17/8" on centers & 13/16" from ends.

STANDARD FINISH:

All Power-Strut fittings are available in painted green or electro-galvanized finish.

POWER-STRUT® DEFENDER™ FINISH [DF]:

Power-Strut Defender is a combination of two proprietary material coatings conforming to ASTM standards A1046 and A1059. It features unique self-healing properties.



ORDERING INFORMATION:

When ordering, add the length or size and finish to the part number.

Project: _____ Architect / Engineer: _____ Date: _____ Phone: _____ Contractor: _____ Address: _____ _____ Notes 1: _____ _____ Notes 2: _____ _____	Approval Stamp:
---	--