



Catalog Number See Table
UPC Number
Description Dual Rated Aluminum Split Bolt
 4/0 Thru 500 MCM



Features


- Manufactured from High Strength High Conductivity Aluminum Alloy
- Electro-Tin Plated
- CU-AL Dual rated for AL/AL, AL/CU, CU/CU Applications
- Conductor Spacer to accommodate dissimilar conductors

General

Conductor Size: 4/0 - 500 MCM
Material: 6061-T6 Aluminum Alloy
Finish: Electro-Tin Plating

Dimension Information

See Table



Specifications

Temperature Rating 75° C
Voltage Rating 600
Flammability Rating N/A
Amp Rating To Conductor

Packaging

Box Qty See Table

Certifications

UL UL 486B Dual Rated
CSA Yes
RoHS N/A

Cat No.	AWG	Max Run To Max Tap	Min Run To Min Tap	Max Run To Min Tap	Min Equal Tap & Run	Temp Rating	Torque In-Lb	B	C	H	L	R	V	W	Box Qty
90422	36617	4/0-4/0	40580	4/0-6		90°C	500	1.17	1.5	1.13	2.75	1.17	0.56	1.73	30
90424	350	350-350	1/0-4	350-4		90°C	650	1.66	1.68	1.48	2.99	1.5	0.696	1.93	12
90426	500	500-500	400-2	500-2		90°C	825	1.95	2.1	1.7	3.29	1.71	0.85	2.3	12