

Clear Insulated Connectors



- ▶ Clear Insulation
- ▶ 6061-T6 Aluminum
- ▶ Insulated with Rugged High-Dielectric Plastisol Dipped Coating
- ▶ Pre-filled with Oxide Inhibitor
- ▶ Easy Re-Entry for Changes, Inspection or Troubleshooting
- ▶ Plugs Marked with Connector Max Wire Size for easy ID
- ▶ CU9AL Dual Rated for use with Copper and/or Aluminum Wire
- ▶ One Wire Per Terminal
- ▶ Temperature Range of -49°F to 194°F (-45° to 90°C)
- ▶ 600 volt
- ▶ Rated For Use with 90°C Cables
- ▶ ANSI C119.4 & UL 486B listed

Insulated In-line Splices



Dimensions = Inches

Cat. No.	Wire Range	Allen Hex	Length	Width	Height	Box Qty
97302	2 - 14	Slotted	3.46	.82	1.62	15
97304	2/0 - 2	3/16	3.50	.99	1.95	12
97305	250 - 6	1/4	4.26	1.26	2.28	4
97306	350 - 6	5/16	5.21	1.33	2.63	4
97307	500 - 6	5/16	5.99	1.84	3.19	5

Insulated Dual Side Entry Splices



Dimensions = Inches

Cat. No.	No. of Ports	Wire Range	Allen Hex	Length	Width	Height	Box Qty				
97312	2	4 - 14	Slotted	1.13	1.16	1.31	12				
97314	3			1.56			12				
97316	4			2.06			6				
97318	5			2.56			6				
97320	6			3.06			4				
97322	8	4.06	2								
97332	2	2-14	Slotted	1.15	1.20	1.50	15				
97333	3			1.60			12				
97334	4			2.02			6				
97335	5			2.43			5				
97336	6			2.85			4				
97338	8			3.69			3				
97352	2			2/0 - 6			3/16	1.63	1.75	1.38	10
97354	3							2.38			8
97356	4	3.13	6								
97358	5	3.88	4								
97360	6	4.63	4								
97362	8	6.13	3								
97392	2	250- 6	5/16	2.13	2.63	2.13	6				
97394	3			3.13			6				
97396	4			4.13			3				
97398	5			5.00			2				
97400	6			6.00			3				
97402	8			8.00			3				
97412	2			350 - 6			3/8	2.25	3.13	2.50	4
97414	3							3.25			3
97416	4							4.25			4
97418	5							5.25			4
97420	6	6.25	2								
97422	8	8.25	3								
97432	2	500 - 6	3/8		2.88	3.19		2.75			4
97434	3				4.13						4
97436	4			5.38	3						
97438	5			6.63	4						
97440	6			7.88	2						
97442	8			10.38	2						