

# Insulated Splices - Single Side Entry - Mountable



- ▶ Mountable
- ▶ Single Side Entry
- ▶ 6061-T6 Aluminum
- ▶ Insulated with Rugged High-Dielectric Plastisol Dipped Coating
- ▶ Pre-filled with Oxide Inhibitor
- ▶ Easy Re-Entry for Changes, Inspection or Troubleshooting
- ▶ Plugs Marked with Connector Max Wire Size for easy identification
- ▶ CU9AL Dual Rated for use with Copper and/or Aluminum Wire
- ▶ One Wire Per Terminal
- ▶ Temperature Range of -49°F to 194°F (-45° to 90°C)
- ▶ 600 Volts
- ▶ Rated For Use with 90°C Cables
- ▶ ANSI C119.4 & UL 486B listed



Dimensions = Inches

| Cat. No. | Wire Ports | Wire Range | Allen Hex | Length | Height |
|----------|------------|------------|-----------|--------|--------|
| 97712    | 2          |            |           | 1.97   |        |
| 97714    | 4          | 4-14       | 1/8       | 2.82   | 1.45   |
| 97716    | 6          |            |           | 3.65   |        |
| 97732    | 2          |            |           | 3.01   |        |
| 97733    | 3          |            |           | 3.69   |        |
| 97734    | 4          | 2/0-14     | 7/32      | 4.36   | 1.50   |
| 97735    | 5          |            |           | 4.74   |        |
| 97736    | 6          |            |           | 5.41   |        |
| 97742    | 2          |            |           | 3.85   |        |
| 97743    | 3          |            |           | 4.71   |        |
| 97744    | 4          | 250-6      | 5/16      | 5.57   | 2.10   |
| 97745    | 5          |            |           | 6.43   |        |
| 97746    | 6          |            |           | 7.29   |        |
| 97752    | 2          |            |           | 4.57   |        |
| 97753    | 3          |            |           | 5.62   |        |
| 97754    | 4          | 350-6      | 5/16      | 6.67   | 2.50   |
| 97755    | 5          |            |           | 7.72   |        |
| 97756    | 6          |            |           | 8.77   |        |
| 97762    | 2          |            |           | 5.63   |        |
| 97763    | 3          |            |           | 7.11   |        |
| 97764    | 4          | 600-4      | 5/16      | 8.47   | 2.90   |
| 97765    | 5          |            |           | 9.83   |        |
| 97766    | 6          |            |           | 11.18  |        |
| 97772    | 2          |            |           | 6.19   |        |
| 97773    | 3          |            |           | 7.75   |        |
| 97774    | 4          | 750-250    | 3/8       | 9.18   | 3.60   |
| 97775    | 5          |            |           | 10.60  |        |
| 97776    | 6          |            |           | 12.03  |        |