Recessed Lighting Retrofit Kit LED Series














72602



- ▶ LED Retrofit Kits for Recessed Downlighting
- ▶ Can be installed in most 4", 5" & 6" Downlights
- ▶ Aluminum Housing/Trim Paintable
- ▶ Simple Screw-In Installation
- ▶ In-Line Pluggable Disconnect Included
- Guaranteed Single Bin Color Consistency with enhanced illumination uniformity
- ▶ Dimmable Down to 10%
- ▶ Compatible with most household dimmers
- ▶ Input Voltage: 120VAC
- ▶ Operating Temperature: 32°F to 140°F
- ▶ 50,000+ Hour LED Life Expectancy
- ▶ Wet Location Rated
- ▶ 5 year Warranty

72	260	02	&	72	26	04	L	οw	≡ vei le l	r P	ric	cir	ng	
														•

Cat No.	Style	Size	Color Temperature	Watts	Delivered Lumens	CRI	Replaces Incandescent	Case Qty	
		,	,	Smoot	h Style				
72604	Smooth	4"	3000K	10.5	650	90	65W	40	
72605	Smooth	4"	4000K	10.5	650	90	65W	40	
72602	Smooth	5" & 6"	3000K	14.5	1100	90	75W	30	
72603	Smooth	5"& 6"	4000K	14.5	1100	90	75W	30	
72601	Smooth	5"& 6"	5000K	14.5	1200	80	75W	30	
				Baffle Style	(Grooves)				
72607	Baffle	4"	3000K	10.5	650	90	65VV	40	
72608	Baffle	4"	4000K	10.5	650	90	65W	40	
72609	Baffle	5" & 6"	3000K	14.5	1100	90	75VV	30	
72610	Baffle	5"& 6"	4000K	14.5	1100	90	75W	30	
72611	Baffle	5"& 6"	5000K	14.5	1200	80	75W	30	

Surface Mount Lighting Retrofit Kit LED Series







Available July 2016 💵



- Surface Mount
- ▶ Perfect for Residential and Commercial
- ▶ Driverless AC Direct Wired
- ▶ Can install in 4" J-Box & most 5" & 6" Downlights
- ► Hardwire to J-Box OR Screw-In to Recessed Can
- Torsion Spring & Brackets for Can Mounting
- ▶ Aluminum Housing/Trim Paintable
- ▶ In-Line Pluggable Disconnect Included
- Guaranteed Single Bin Color Consistency with enhanced illumination uniformity
- ▶ Dimmable Down to 10%
- ▶ Compatible with most household dimmers
- ▶ Input Voltage: 120VAC
- ▶ Operating Temperature: 32°F to 140°F
- ▶ 50,000+ Hour LED Life Expectancy
- ▶ Wet Location Rated
- ▶ 5 year Warranty

Cat. No.	Size	Color Temperature	Watts Delivered Lumens		CRI	Replaces Incandescent	Case Qty	
72612	6"	3000K	14.5	1100	90+	75W	30	
72613	6"	4000K	14.5	1100	90+	75W	30	
72614	6"	5000K	14.5	1100	90+	75W	30	



