

## Submersible Insulated Splice Connectors



Can be used for any type of splice

- ▶ Designed for use in Direct Burial & Submersible installations such as hand holes, below grade boxes, in the ground or submersed in water
- ▶ Range Taking Design Reduces Inventory
- ▶ AL9CU Dual Rated for Copper & Aluminum Conductors
- ▶ Insulated with High Dielectric Strength Rubber Compound
- ▶ Molded for Precise Fit & supplied with removable access plugs over the hex screws
- ▶ Eliminates the need for Taping, Heat Shrink etc.
- ▶ Abrasion and Chemical Resistant, will not support combustion
- ▶ Meets or exceeds ANSI C119.1 Specifications for a Submersible Connection
- ▶ UL Listed for Wet or Damp Locations, Direct Burial & Submersible per UL486D
- ▶ Rated 600 Volts, Cold Temperature UL tested to 0°F

Cat. No.	Wire Range AWG	Wire Range (inches)	Bolt Size	Dimensions (inches)			Case Qty
				H	W	L	
98012	2/0-14	.365 - .064	3/16	2.13	0.88	5.50	25
98014*	350-12	.58 - .08	5/16	3.16	1.44	8.14	50

\*UL Pending 2015

## Submersible Insulated Pedestal Connectors

UL Pending 2015



Can be used for any type of splice

- ▶ Designed for use in Direct Burial & Submersible installations such as hand holes, below grade boxes, in the ground or submersed in water
- ▶ Range Taking Design Reduces Inventory
- ▶ Dual Rated for Copper & Aluminum Conductors
- ▶ Insulated with High Dielectric Strength Rubber Compound
- ▶ Molded for Precise Fit & supplied with removable access plugs over the hex screws
- ▶ Eliminates the need for Taping, Heat Shrink etc.
- ▶ Abrasion and chemical resistant, Will not support combustion
- ▶ Meets or exceeds ANSI C119.1 Specifications for a Submersible Connection
- ▶ Rated 600 Volts, Cold Temperature UL tested to 0°F

Cat. No.	Number of Ports	Wire Range AWG	Wire Range	Bolt Size	Dimensions (inches)			Case Qty
					H	W	L	
98023	3	350-12	.58" - .08"	5/16	2.46	4.06	3.63	25
98024	4	350-12	.58" - .08"	5/16	2.46	4.06	4.75	20
98026	6	350-12	.58" - .08"	5/16	2.46	4.06	7.00	20
98033	3	600-12	.89" - .08"	5/16	3.13	5.46	4.87	12
98034	4	600-12	.89" - .08"	5/16	3.13	5.46	6.56	12
98036	6	600-12	.89" - .08"	5/16	3.13	5.46	9.94	6
98038	8	600-12	.89" - .08"	5/16	3.13	5.46	13.31	4

## Submersible Insulated Streetlighting Connectors



Fig 1



Fig 2

- ▶ Designed for use in Direct Burial & Submersible Streetlighting applications such as hand holes, below grade boxes, in ground or water
- ▶ Range Taking Design Reduces Inventory
- ▶ AL9CU Dual Rated for Copper & Aluminum Conductors
- ▶ Insulated with High Dielectric Strength Rubber Compound
- ▶ Molded for Precise Fit & supplied with removable access plugs over the hex screws
- ▶ Eliminates the need for Taping, Heat Shrink etc.
- ▶ Abrasion and chemical resistant, will not support combustion
- ▶ Meets or exceeds ANSI C119.1 Specifications for a Submersible Connection
- ▶ UL Listed for Wet Locations, Direct Burial & Submersible per UL486D
- ▶ Rated 600 Volts, Cold Temperature UL tested to 0°F

Cat. No.	Fig	Number of Ports	Wire Range AWG	Wire Range (inches)	Bolt Size	Dimensions (inches)			Case Qty
						H	W	L	
98042	1	2	2/0-14	.365 - .064	3/16	2.13	2.75	1.80	40
98043	1	3	2/0-14	.365 - .064	3/16	2.13	2.75	2.65	25
98044	1	4	2/0-14	.365 - .064	3/16	2.13	2.75	3.49	25
98046	1	6	2/0-14	.365 - .064	3/16	2.13	2.75	5.17	25
98052	2	3	2/0-14	.365 - .064	3/16	2.13	4.25	2.65	25

Can be used for any type of splice