

Streetlighting In-line Mechanical Break-Away Disconnect Kits



67064 Fusible



67065 Non-Fused

Kit Includes:

EPDM Rubber Housing, Fuse Clips, Connecting Link (as Required), Silicone Lubricant. Fuse Not Included.

- ▶ Break-Away Design Separates Under Tension so wires don't break
- ▶ Ensures a Fully Insulated, Watertight and Submersible connection
- ▶ Fuse or Connecting Link stays in load side when separated
- ▶ Approved for a wide range of Aluminum or Copper conductors
- ▶ Accommodates Insulated Wire up to .38" Diameter
- ▶ Accepts Standard Cartridge Fuses 13/32" X 1-1/2" - No Glass Fuses
- ▶ 30A 600V Max

Cat. No.	Fused/ Non-Fused	Wire Range Run	Wire Range Tap	Dimensions (inches)		Case Qty
				Dia.	L	
67064	Fused	#12 - #4	#12 - #4	1-1/16	5-3/8	25
67065	Non-Fused	#12 - #4	#12 - #4	1-1/16	5-3/8	25

Streetlighting Y-Type Mechanical Break-Away Disconnect Kits



67066 Fusible



67067 Non-Fused

Kit Includes:

EPDM Rubber Housing, Fuse Clips, Connecting Link (as Required), Silicone Lubricant. Fuse Not Included.

- ▶ Break-Away Design Separates Under Tension so wires don't break
- ▶ Ensures a Fully Insulated, Watertight and Submersible connection
- ▶ Fuses or Connecting Link stay in load side when separated
- ▶ Approved for a wide range of Aluminum or Copper conductors
- ▶ Accommodates Insulated Wire up to .78" Dia.(Run) .38" Dia.(Tap)
- ▶ Accepts Standard Cartridge Fuses 13/32" X 1-1/2" - No Glass Fuses
- ▶ 30A 600V Max

Cat. No.	Fused/ Non-Fused	Wire Range Run	Wire Range Tap	Dimensions (inches)		Case Qty
				Dia.	L	
67066	Fused	#14 - #2	#12 - #4	1-5/8"	9-3/4"	25
67067	Non-Fused	#14 - #2	#12 - #4	1-5/8"	9-3/4"	10

Streetlighting In-line Compression Break-Away Disconnect Kits



Fusible



Non-Fused

Kit Includes:

EPDM Rubber Housing, Fuse Clips, Connecting Link (as Required), Silicone Lubricant. Fuse Not Included.

- ▶ Break-Away Design Separates Under Tension so wires don't break
- ▶ Compression Connectors are durable & maintenance free
- ▶ Ensures a Fully Insulated, Watertight and Submersible connection
- ▶ Fuse or Connecting Link stays in load side when separated
- ▶ Approved for a wide range of Aluminum or Copper conductors
- ▶ Accommodates Insulated Wire up to .38" Diameter
- ▶ Accepts Standard Cartridge Fuses 13/32" X 1-1/2" - No Glass Fuses
- ▶ 30A 600V Max

Cat. No.	Fused/ Non-Fused	Wire Range Run	Wire Range Tap	Dimensions (inches)		Case Qty
				Dia.	L	
67068	Fused	#14 - #6	#14 - #6	1-1/16	5-3/8	25
67069	Fused	#4 - #2	#4 - #2	1-1/16	5-3/8	25
67070	Non-Fused	#14 - #6	#14 - #6	1-1/16	5-3/8	25
67071	Non-Fused	#4 - #2	#4 - #2	1-1/16	5-3/8	25

Streetlighting Y-Type Compression Break-Away Disconnect Kits



Fusible



Non-Fused

Kit Includes:

EPDM Rubber Housing, Fuse Clips, Connecting Link (as Required), Silicone Lubricant. Fuse Not Included.

- ▶ Break-Away Design Separates Under Tension so wires don't break
- ▶ Mechanical Run & Compression Tap Connectors
- ▶ Ensures a Fully Insulated, Watertight and Submersible connection
- ▶ Fuses or Connecting Link stay in load side when separated
- ▶ Approved for a wide range of Aluminum or Copper conductors
- ▶ Accommodates Insulated Wire up to .78" Dia.(Run) .38" Dia.(Tap)
- ▶ Accepts Standard Cartridge Fuses 13/32" X 1-1/2" - No Glass Fuses
- ▶ 30A 600V Max

Cat. No.	Fused/ Non-Fused	Wire Range Run	Wire Range Tap	Dimensions (inches)		Case Qty
				Dia.	L	
67072	Fused	#14 - #2	#14 - #6	1-5/8"	9-3/4"	25
67073	Fused	#14 - #2	#4 - #2	1-5/8"	9-3/4"	20
67074	Non-Fused	#14 - #2	#14 - #6	1-5/8"	9-3/4"	25
67075	Non-Fused	#14 - #2	#4 - #2	1-5/8"	9-3/4"	25