





- ► Superior Quality Exit Unit Combined with LED Energy Saving Technology In a Low-Profile, Unobtrusive Design
- ▶ Available in Standard AC Only & Emergency (Battery Backup) Units
- ► Completely Self-Contained
- ► Fully Automatic Operation
- ► Compact, Low Profile Design in Neutral Finish
- ▶ Push to Test Switch in Battery Backup Units
- ► Automatic, Low Voltage Disconnect (LVD)
- ▶ 120 or 277 VAC Operation
- ► Charge Rate/Power On LED Indicator Light
- ► Energy Consumption of Less than 4 Watts for Red Letters and Less than 2 Watts for Green Letters
- ► Injection-Molded, UL 94 V-0 Flame Retardant, High Impact Thermoplastic Housing
- ▶ Listed for Damp Location
- Universal Canopy Mount & 2 Face Plates for Side or Top Installation
- ▶ 2.4V 400maH Ni-Cad Battery On Standard Units
- ➤ 3.6V 1800maH Ni-Cad Battery On High Output & Remote Capable Units
- ▶ 90 Minute Minimum Battery Run Time
- ▶ Models 73022 73025 have Remote Capability for up to 2 Additional LED Remote Lamp Heads 2 heads - 3 hours operation (Base Unit)
  - 3 heads 2 hours operation (Base Unit + 1 Head) 4 heads - 1.5 hours operation (Base Unit + 2 Heads)
- ▶ UL 924 Listed
- ▶ 5 Year Warranty

Cat. No.	LED Color	Housing	Battery Backup	Case Qty
Standard				
73010	Red	White	No	6
73012	Red	White	Yes	6
73013	Red	Black	Yes	6
73014	Green	White	No	6
73016	Green	White	Yes	6
73017	Green	Black	Yes	6
Remote Capable (Use only LED Remote Heads)				
73022	Red	White	Yes	6
73023	Red	Black	Yes	6
73024	Green	White	Yes	6
73025	Green	Black	Yes	6
2 Circuit Unit Wired For AC Power & DC Generator Backup				
73026	Red	White	No	6
73028	Green	White	No	6
Standard with Self Diagnostic				
73512	Red	White	Yes	6
73514	Green	White	Yes	6
Remote Capable with Self Diagnostic (Use only LED Remote Heads)				
73516	Red	White	Yes	6
73518	Green	White	Yes	6