

Thin Wall Heat Shrink Tubing - 4' Length



- ▶ Flexible Polyolefin Heat Shrink Tubing
- ▶ 2:1 Shrink Ratio
- ▶ 600 Volt
- ▶ 257°F (125°C) Continuous Operation
- ▶ For Insulating, Wire Harness, Wire Bundling, Splicing & Terminations
- ▶ UL 224 Recognized

Dimensions = Inches

Cat. No.	Length	Color	Diameter Before Shrinking	Diameter After Shrinking	Bag Qty
68072	4 Ft	Black	.078	.029	1
68074	4 Ft	Black	.098	.039	1
68076	4 Ft	Black	.137	.059	1
68078	4 Ft	Black	.211	.098	1
68080	4 Ft	Black	.250	.117	1
68082	4 Ft	Black	.367	.176	1
68084	4 Ft	Black	.484	.234	1
68086	4 Ft	Black	.827	.390	1
68088	4 Ft	Black	1.26	.590	1
68382	4 Ft	Clear	.078	.029	1
68383	4 Ft	Clear	.098	.039	1
68384	4 Ft	Clear	.137	.059	1
68385	4 Ft	Clear	.211	.098	1
68386	4 Ft	Clear	.250	.117	1
68387	4 Ft	Clear	.367	.176	1
68388	4 Ft	Clear	.484	.234	1
68389	4 Ft	Clear	.827	.390	1
68391	4 Ft	Red	.078	.029	1
68392	4 Ft	Red	.098	.039	1
68393	4 Ft	Red	.137	.059	1
68394	4 Ft	Red	.211	.098	1
68395	4 Ft	Red	.250	.117	1
68396	4 Ft	Red	.367	.176	1
68397	4 Ft	Red	.484	.234	1
68398	4 Ft	Red	.827	.390	1
68399	4 Ft	Red	1.26	.590	1
68400	4 Ft	Green	.078	.029	1
68401	4 Ft	Green	.098	.039	1
68402	4 Ft	Green	.137	.059	1
68403	4 Ft	Green	.211	.098	1
68404	4 Ft	Green	.250	.117	1
68405	4 Ft	Green	.367	.176	1
68406	4 Ft	Green	.484	.234	1
68407	4 Ft	Green	.827	.390	1
68408	4 Ft	Green	1.26	.590	1
68409	4 Ft	White	.078	.029	1
68410	4 Ft	White	.098	.039	1
68411	4 Ft	White	.137	.059	1
68412	4 Ft	White	.211	.098	1
68413	4 Ft	White	.250	.117	1
68414	4 Ft	White	.367	.176	1
68415	4 Ft	White	.484	.234	1
68416	4 Ft	White	.827	.390	1
68417	4 Ft	White	1.26	.590	1
68418	4 Ft	Blue	.078	.029	1
68419	4 Ft	Blue	.098	.039	1
68420	4 Ft	Blue	.137	.059	1
68421	4 Ft	Blue	.211	.098	1
68422	4 Ft	Blue	.250	.117	1
68423	4 Ft	Blue	.367	.176	1
68424	4 Ft	Blue	.484	.234	1
68425	4 Ft	Blue	.827	.390	1
68426	4 Ft	Blue	1.26	.590	1