


# Vinyl Insulated Multiple-Stud Ring Terminals



## MAXIMUM ELECTRIC CURRENT:


Awg	22	20	18	16	14	12	10
Amp	9	12	17	18	30	35	50

**MAXIMUM ELECTRIC RATING:** 167°F(75°C) 600 Volts

**INSULATION MATERIAL:** Vinyl

**TERMINAL MATERIAL:** Electro-Tin Plated Copper

**FEATURES:** Serrated Barrel, Expanded Insulation



Dimensions = Inches

Cat. No.	Color	Wire Size AWG	Stud Size	d2	W	F	L	E	D	d1	T	Bag Qty	Master Bag Qty
11452	Red	22-16	#6	.146									
	Red	22-16	#8	.169	.339	.311	1.012	.441	.157	.067	.030	100	1000
	Red	22-16	#10	.209									
11454	Blue	16-14	#6	.146									
	Blue	16-14	#8	.169	.339	.311	1.024	.453	.177	.091	.031	100	1000
	Blue	16-14	#10	.209									
11456	Yellow	12-10	#6	.146									
	Yellow	12-10	#8	.169	.390	.350	1.205	.555	.248	.134	.039	100	1000
	Yellow	12-10	#10	.209									

# Nylon Insulated Multiple-Stud Ring Terminals



## MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	9	12	17	18	30	35	50


**MAXIMUM ELECTRIC RATING:** 221°F (105°C) 600 Volts

**INSULATION MATERIAL:** Nylon

**TERMINAL MATERIAL:**

Electro-Tin Plated Copper - Brazed Seam

**FEATURES:** Serrated Barrel, Expanded Insulation



Dimensions = Inches

Cat. No.	Color	Wire Size AWG	Stud Size	d2	W	F	L	E	D	d1	T	Bag Qty	Master Bag Qty
11462	Red	22-16	#6	.146									
	Red	22-16	#8	.169	.339	.311	.996	.433	.157	.067	.030	100	1000
	Red	22-16	#10	.209									
11464	Blue	16-14	#6	.146									
	Blue	16-14	#8	.169	.339	.311	.996	.433	.177	.091	.031	100	1000
	Blue	16-14	#10	.209									
11466	Yellow	12-10	#6	.146									
	Yellow	12-10	#8	.169	.390	.350	1.154	.512	.252	.134	.039	100	1000
	Yellow	12-10	#10	.209									