



MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	9	12	17	18	30	35	50

TERMINAL MATERIAL:

Electro-Tin Plated Tubular Copper

INSULATION MATERIAL: Nylon Insulation

FEATURES: Flared Barrel, Expanded Insulation

MAXIMUM ELECTRIC RATING: 221°F(105°C) 600V

COLOR CODE: DIN Standard

Dimensions = Inches

Cat. No.	Wire Size AWG	Color	F	B	L	W	D	C	Bag Qty	Master Bag Qty
12702	26	Yellow	.236	.173	.409	.075	.043	.031	100	1000
12704	26	Yellow	.315	.173	.488	.075	.043	.031	100	1000
12706	24	Turquoise	.236	.173	.409	.075	.043	.031	100	1000
12708	24	Turquoise	.315	.173	.488	.075	.043	.031	100	1000
12710	22	White	.236	.236	.472	.102	.051	.039	100	1000
12712	22	White	.315	.236	.551	.102	.051	.039	100	1000
12714	22	White	.394	.236	.630	.102	.051	.039	100	1000
12716	20	Grey	.236	.248	.472	.110	.059	.047	100	1000
12718	20	Grey	.315	.248	.551	.110	.059	.047	100	1000
12720	20	Grey	.394	.260	.630	.110	.059	.047	100	1000
12722	20	Grey	.472	.260	.709	.110	.059	.047	100	1000
12724	18	Red	.236	.248	.472	.118	.067	.055	100	1000
12726	18	Red	.315	.248	.551	.118	.067	.055	100	1000
12728	18	Red	.394	.248	.630	.118	.067	.055	100	1000
12730	18	Red	.472	.248	.709	.118	.067	.055	100	1000
12732	16	Black	.315	.248	.551	.138	.079	.067	100	1000
12734	16	Black	.394	.248	.630	.138	.079	.067	100	1000
12736	16	Black	.472	.248	.709	.138	.079	.067	100	1000
12738	16	Black	.709	.248	.945	.138	.079	.067	100	1000
12740	14	Blue	.315	.165	.551	.165	.098	.087	100	1000
12742	14	Blue	.472	.165	.709	.165	.098	.087	100	1000
12746	14	Blue	.709	.165	.945	.165	.098	.087	100	1000
12748	12	Grey	.394	.189	.669	.189	.126	.110	100	1000
12750	12	Grey	.472	.189	.787	.189	.126	.110	100	1000
12752	12	Grey	.709	.189	1.024	.189	.126	.110	100	1000
12754	10	Yellow	.472	.248	.787	.248	.154	.138	100	1000
12756	10	Yellow	.709	.248	1.024	.248	.154	.138	100	1000
12758	8	Red	.472	.299	.886	.299	.193	.177	100	-
12760	8	Red	.709	.299	1.102	.299	.193	.177	100	-
12762	6	Blue	.472	.346	.945	.524	.236	.220	100	-
12764	6	Blue	.709	.346	1.102	.524	.236	.220	100	-
12766	4	Yellow	.630	.441	1.102	.441	.303	.287	100	-
12768	4	Yellow	.709	.441	1.181	.441	.303	.287	100	-
12770	4	Yellow	.886	.441	1.417	.441	.303	.287	100	-
12772	2	Red	.630	.500	1.181	.500	.343	.327	100	-
12774	2	Red	.709	.500	1.245	.500	.343	.327	100	-
12776	2	Red	.984	.500	1.535	.500	.343	.327	100	-