



MAXIMUM ELECTRIC CURRENT:

Awg	8	6	4	2
Amp	70	95	125	170

MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL:

Electro-Tin Plated Copper - Brazed Seam

FEATURES: Serrated Barrel, Expanded Insulation

Dimensions = Inches

Cat. No.	Color	Wire Size AWG	Stud Size	d2	W	F	L	E	D	d1	T	Bag Qty
11376	Red	8	#6	.146	.315	.366	1.142	.630	.315	.177	.047	100
11378	Red	8	#8	.169	.472	.366	1.232	.630	.315	.177	.047	100
11380	Red	8	#10	.209	.472	.366	1.232	.630	.315	.177	.047	100
11382	Red	8	1/4	.252	.472	.366	1.232	.630	.315	.177	.047	100
11384	Red	8	5/16	.331	.591	.543	1.469	.630	.315	.177	.047	100
11386	Red	8	3/8	.413	.591	.543	1.469	.630	.315	.177	.047	100
11388	Red	8	1/2	.512	.787	.591	1.614	.630	.315	.177	.047	100
11390	Blue	6	#8	.169	.472	.524	1.606	.846	.433	.228	.059	100
11392	Blue	6	#10	.209	.472	.524	1.606	.846	.433	.228	.059	100
11394	Blue	6	1/4	.252	.472	.524	1.606	.846	.433	.228	.059	100
11396	Blue	6	5/16	.331	.630	.559	1.713	.846	.433	.228	.059	100
11398	Blue	6	3/8	.413	.630	.559	1.713	.846	.433	.228	.059	100
11400	Blue	6	7/16	.453	.866	.780	2.047	.846	.433	.228	.059	100
11402	Blue	6	1/2	.512	.866	.780	2.047	.846	.433	.228	.059	100
11404	Yellow	4	#8	.169	.480	.594	1.780	.945	.512	.303	.067	100
11406	Yellow	4	#10	.209	.480	.594	1.780	.945	.512	.303	.067	100
11408	Yellow	4	1/4	.252	.480	.614	1.772	.945	.512	.303	.067	100
11410	Yellow	4	5/16	.331	.650	.531	1.791	.945	.512	.303	.067	100
11412	Yellow	4	3/8	.413	.650	.531	1.791	.945	.512	.303	.067	100
11414	Yellow	4	7/16	.453	.866	.776	2.146	.945	.512	.303	.067	100
11416	Yellow	4	1/2	.512	.866	.776	2.146	.945	.512	.303	.067	100
11418	Red	2	#10	.209	.602	.685	2.047	1.063	.571	.370	.071	100
11420	Red	2	1/4	.252	.602	.685	2.047	1.063	.571	.370	.071	100
11422	Red	2	5/16	.331	.602	.685	2.047	1.063	.571	.370	.071	100
11424	Red	2	3/8	.413	.602	.685	2.047	1.063	.571	.370	.071	100
11426	Red	2	7/16	.453	.866	.697	2.193	1.063	.571	.370	.071	100
11428	Red	2	1/2	.512	.866	.697	2.193	1.063	.571	.370	.071	100