



- ▶ Made from UL approved Nylon 6/6
- ▶ Normal service temperature range -40° to 185°F (-40° to 85°C)
- ▶ Flammability rating UL94V-2
- ▶ 20087 & 20089 UL181b-C listed for use with UL non-metallic air ducts & air connectors

Dimensions = Inches

Cat. No.	Tensile Strength (Lbs.)	Length	Width	Maximum Bundle Diameter	Bag Qty	Master Bag Qty
20012	18	3	.094	.71	100	1000
20014	18	4	.098	.99	100	1000
20016	18	4-3/4	.098	1.18	100	1000
20018	18	6	.098	1.38	100	1000
20020	18	6-1/2	.098	1.73	100	1000
20022	18	8	.098	2.17	100	1000
20032	40	4-3/4	.125	1.18	100	1000
20034	40	6	.140	1.54	100	1000
20036	40	8	.125	2.17	100	1000
20038	40	10	.140	2.91	100	1000
20040	40	11-3/4	.140	3.35	100	1000
20052	50	7	.156	1.93	100	1000
20054	50	8	.179	2.17	100	1000
20056	50	11	.187	3.19	100	1000
20058	50	14-1/2	.187	4.02	100	1000
20060	50	17	.187	4.92	100	100
20072	120	8	.296	2.17	100	100
20074	120	11-3/4	.296	3.19	100	100
20076	120	15	.296	4.33	100	100
20082	175	17-3/4	.312	5.24	100	100
20084	175	21-5/8	.312	6.54	100	100
20085	175	24	.351	7.28	100	100
20086	175	30	.351	9.29	100	100
20087	175	36	.351	10.63	100	100
20088	175	46	.351	14.17	100	100
20089	175	48	.351	14.96	100	100
20092	250	11	.500	3.19	100	100
20094	250	21	.500	6.54	100	100
20096	250	28-3/4	.500	8.86	100	100
20098	250	40	.500	12.48	100	100

Nylon Cable Ties - 1000 Piece Bulk Pack

Dimensions = Inches

Cat. No.	Tensile Strength (Lbs.)	Length	Width	Maximum Bundle Diameter	Bag Qty
20112	18	4	.098	.87	1000
20118	40	6	.094	1.42	1000
20120	40	8	.126	2.09	1000
20122	40	11-3/4	.142	3.23	1000
20124	50	7	.142	1.81	1000
20126	50	8	.181	2.05	1000
20128	50	11	.189	3.03	1000
20130	50	14-1/2	.189	4.13	1000