
MORRIS






- ▶ Protect electrical cables, ropes, utility lines passing through metal
- ▶ 1/8" maximum steel thickness
- ▶ Made from UL approved Nylon 6/6, 94V-2

Dimensions = Inches

					0.01.0
Cat. No.	Mounting Hole Diameter	Inside Diameter	Head Diameter	Overall Height	Bag Qty
22311	.28	.23	.34	.24	10
22312	.31	.23	.37	.31	10
22314	.37	.25	.47	.41	10
22316	.50	.32	.57	.41	10
22317	.55	.45	.67	.41	10
22318	.63	.48	.73	.41	10
22320	.75	.56	.85	.41	10
22322	.87 (1/2" Trade)	.68	.94	.45	10
22324	.99	.75	1.10	.45	10
22326	1.17 (3/4" Trade)	.95	1.31	.45	10
22328	1.50	1.14	1.62	.45	10
22330	1.72	1.39	1.88	.46	10
22332	1.97	1.64	2.15	.46	10



Snap Bushings with Shutters



- ▶ Flexible shutters to accommodate a variety of cable & hose sizes from a minimum of 1/8" to a maximum as shown in the table
- ▶ Shutters absorb vibration & cushion cables, tubes, etc.
- ▶ Fingertip pressure snap-locks the bushing into the mounting hole
- ▶ Universal design to hold various cable ranges
- ▶ 1/8" maximum steel thickness
- ▶ Made from UL approved Nylon 6/6, 94V-2


Dimensions = Inches

	Billionolone - mark				
Cat. No.	Mounting Hole Diameter	Max Cable Size ID	Head Diameter	Overall Height	Bag Qty
22342	.63	.44	.72	.41	10
22344	.75	.50	.86	.39	10
22346	.81	.50	.89	.39	10
22348	.87 (1/2" Trade)	.56	.93	.45	10
22350	1.00	.80	1.12	.44	10
22352	1.09 (3/4" Trade)	.88	1.21	.44	10
22354	1.35 (1" Trade)	1.15	1.48	.44	10
22356	1.50	1.22	1.61	.43	10



Snap Bushings (Open/Closed)





- ▶ 1/8" maximum steel thickness
- ▶ Finger tip pressure snap-locks the bushing into the mounting hole
- ▶ Can be applied where cables are already installed
- ▶ Can accommodate cables too large to fit through the inside diameter of a standard bushing
- ▶ Made from UL approved Nylon 6/6, 94V-2

Dimensions	=	Inch	es
	_	111011	-

		Dimensions = inches			
Cat. No.	Mounting Hole Diameter	Inside Diameter	Head Diameter	Overall Height	Bag Qty
22362	3/8	.26	.42	.375	10
22364	1/2	.31	.56	.375	10
22366	5/16	.45	.70	.375	10
22368	3/4	.52	.80	.375	10
22370	7/8	.67	.92	.375	10
22372	1	.80	1.06	.375	10



