

# Ultraviolet Black Nylon Cable Ties



- ▶ Carbonate 'A' added for greater resistance to Ultra Violet in outdoor usage
- ▶ Made from UL approved Nylon 6/6
- ▶ Normal service temperature range -40° to 185°F (-40° to 85°C)
- ▶ Flammability rating UL94V-2

Dimensions = Inches

Cat. No.	Tensile Strength (Lbs.)	Length	Width	Maximum Bundle Diameter	Bag Qty	Master Bag Qty
20212	18	3	.094	.71	100	1000
20214	18	4	.098	.99	100	1000
20216	18	4-3/4	.098	1.18	100	1000
20218	18	6	.098	1.38	100	1000
20220	18	6-1/2	.098	1.73	100	1000
20222	18	8	.098	2.17	100	1000
20232	40	4-3/4	.125	1.18	100	1000
20234	40	6	.140	1.54	100	1000
20236	40	8	.125	2.17	100	1000
20238	40	10	.140	2.91	100	1000
20240	40	11-3/4	.140	3.35	100	1000
20252	50	7	.156	1.93	100	1000
20254	50	8	.179	2.17	100	1000
20256	50	11	.187	3.19	100	1000
20258	50	14-1/2	.187	4.02	100	1000
20260	50	17	.187	4.92	100	100
20272	120	8	.296	2.17	100	100
20274	120	11-3/4	.296	3.19	100	100
20276	120	15	.296	4.33	100	100
20282	175	17-3/4	.312	5.24	100	100
20284	175	21-5/8	.312	6.54	100	100
20285	175	24	.351	7.28	100	100
20286	175	30	.351	9.29	100	100
20287	175	36	.351	10.63	100	100
20288	175	46	.351	14.17	100	100
20289	175	48	.351	14.96	100	100
20292	250	11	.500	3.19	100	100
20294	250	21	.500	6.54	100	100
20296	250	28-1/2	.500	8.86	100	100
20298	250	40	.500	12.48	100	100

# Ultraviolet Black Nylon Cable Ties - 1000 Piece Bulk Pack



Dimensions = Inches

Cat. No.	Tensile Strength (Lbs.)	Length	Width	Maximum Bundle Diameter	Bag Qty
20152	18	4	.098	.87	1000
20158	40	6	.098	1.42	1000
20160	40	8	.126	2.09	1000
20162	40	11-3/4	.142	3.23	1000
20164	50	7	.142	1.81	1000
20166	50	8	.181	2.05	1000
20168	50	11	.189	3.03	1000
20170	50	14-1/2	.189	4.13	1000