

Master Boot Universal Roof Flashings



- ▶ Can be used with any type of Corrugated Roofing material, ie: asphalt, plastic, tile, rubber, metal, etc. (not for hot mopped or built-up roofs)
- ▶ Self-Sealing Step-Cone Boot made of Premium Grade E.P.D.M. Rubber, which gives it maximum resistance to weathering due to ozone & UV light
- ▶ Flexible Aluminum Alloy Aim assures a formed fit and corrosion resistance - excellent for Ribbed Metal Roofs
- ▶ Provides a Permanent Seal that is unaffected by expansion/contraction, vibration, ice, snow, hailstones, etc.
- ▶ Installs in about 10 minutes
- ▶ Excellent for Wall Penetrations - weathertight and airtight, inside or outside
- ▶ Easily customized with sharp knife/scissors to accommodate a broad range of diameters
- ▶ Slides over vent pipe & conforms to any roof pitch

Cat. No.	Outside Diameter of Pipe to be Flashing	Base		Case Qty	Wt/ Case
		Length	Width		
G16250	1/8" to 3/4"	2-1/4"	2-1/4"	12	2
G16251	1/4" to 2-3/4"	4-1/2"	4-1/2"	6	2
G16252	7/8" to 4"	6"	6"	6	3
G16253	1/4" to 5-3/4"	8"	8"	6	4

Retrofit Roof Flashings



- ▶ Designed for Applications where Continuous Pipes or Obstructions prevent the use of standard flashings
- ▶ Easily installed by wrapping around existing pipe & fastening down onto roof deck
- ▶ The Pliable Cone & Stainless Steel Closure can easily be trimmed to the exact diameter of pipe to be flashed
- ▶ Unique Stainless Steel Closure effectively resists corrosion & provides a positive weatherproof seal
- ▶ Corrosion-Resistant Aluminum Base can be easily shaped to conform to most roof profiles
- ▶ Made of Flexible, Weatherproof E.P.D.M. Rubber Cone, markings in inches & millimeters
- ▶ Insulates the pipe from building movement caused by expansion, contraction, & vibration
- ▶ -30°F to 250°F continuous service temperature range

Cat. No.	Outside Diameter of Pipe to be Flashing	Base		Case Qty	Wt/ Case
		Length	Width		
G14751	1/4" to 4"	8-3/16"	8-3/16"	10	3
G14752	4" to 9-1/4"	14-1/4"	14-1/4"	5	6
G14753	9-1/4" to 16-1/4"	21-1/2"	21-1/2"	5	11