


Cord Grips - Zinc Die Cast



New! Available November 2014



- ▶ Use to Connect S, SO, ST, SJ, SJO and SJT Cord to a Steel Outlet Box or other Metal Enclosure
- ▶ Neoprene Grommet for a moisture proof seal
- ▶ Simple Installation, cord can be installed without disassembly of the fitting
- ▶ Liquid-tight/Oil-tight/Rain-tight
- ▶ Suitable for NEMA 4 Enclosures and other wet locations
- ▶ Male Tapered NPT Threading
- ▶ Colored Seal allows for Easy Identification

Dimensions = Inches


Cat. No.	Trade Size	Insert Color	Cable Range	Overall Dim.		Inner Box	Outer Box
				A	B		
15450	1/2"	Red	.190 -.260	1.22	1.14	25	250
15451	1/2"	Blue	.260 -.375	1.22	1.14	25	250
15452	1/2"	Green	.375 -.500	1.22	1.14	25	250
15453	3/4"	Green	.375 -.500	1.34	1.20	25	250
15454	3/4"	Brown	.500 -.625	1.34	1.20	25	250
15455	3/4"	Orange	.625 -.725	1.34	1.20	25	250
15457	1"	Brown	.500 -.650	1.42	1.69	10	100
15458	1"	Orange	.625 -.750	1.42	1.69	10	100
15459	1"	Black	.750 -.880	1.42	1.69	10	100
15460	1"	Purple	.880 -.985	1.42	1.69	10	100

Metal Cable Glands - NPT Thread



Cable Glands Fittings

M34




- ▶ Used to introduce cables or leads into metal housings, or to introduce reinforced cables
- ▶ Designed for use in areas of zone 1(2G) and 21(1D) with no risk of explosion and for cables with and without reinforcement
- ▶ In case of systems or housing manufactured according to NEC, the line or the connecting cable must be introduced by conduits, mounting fittings, etc. with NPT threads
- ▶ Working Temp: -40°F to 212°F
- ▶ Brass Nickel Plated
- ▶ IP 68 (NEMA 6P) rated - Submersible & Dustproof



Cat. No.	Cable Range	Dimensions			Inner Bag Qty	Outer Box Qty
		D1 Thread	GL (Inches)	H (Inches)		
22600	.16" - .32"	3/8"	.59	.83	100	1500
22601	.24" - .48"	1/2"	.51	.94	100	800
22602	.40" - .55"	1/2"	.51	.94	50	600
22603	.51" - .71"	3/4"	.51	.98	50	500
22604	.71" - .99"	1"	.67	1.14	25	400

Metal Cable Glands - Metric Thread



- ▶ Cable Glands with Metric threads are now standard and replacements for the PG Cable Glands
- ▶ Used to introduce cables or leads into metal housings or to introduce reinforced cables
- ▶ Designed for use in areas of zone 1(2G), and 21(1D) with no risk of explosion and for cables with and without reinforcement
- ▶ Working Temp: -40°F to 212°F
- ▶ Brass Nickel Plated
- ▶ IP 68 (NEMA 6P) rated - Submersible & Dustproof



Cat. No.	Cable Range	Dimensions			Inner Bag Qty	Outer Box Qty
		D1 Thread	GL (Inches)	H (Inches)		
22590	.12" - .26"	M12	.26	.75	100	2000
22591	.16" - .32"	M16	.24	.83	100	1500
22592	.20" - .40"	M16	.24	.83	100	1000
22593	.24" - .48"	M20	.24	.91	100	800
22594	.40" - .55"	M20	.24	.91	50	600
22595	.51" - .71"	M25	.28	1.02	50	500
22596	.71" - .99"	M32	.31	1.22	20	400
22597	.87" - 1.26"	M40	.31	1.46	10	160
22598	1.26" - 1.50"	M50	.35	1.46	10	120
22599	1.46" - 1.73"	M63	.39	1.50	10	80