

Auto-Ranging Digital Multimeter with Rubber Holster



- ▶ AC Voltage: 400m/4/40/400/600V+/-0.8%
- ▶ DC Voltage: 400m/4/40/400/600V+/-0.5%
- ▶ DC Current: 400u/4000/20m/40m/400m/10A+/-2%
- ▶ AC Current: 400u/4000/20m/40m/400m/10A+/-2%
- ▶ Resistance: 400/4K/40K/400K/4M/40M +/-0.8%, 2M+/-1%
- ▶ Frequency: 9.999Hz to 9.999MHz+/-3%
- ▶ Auto ranging with Manual Ranging Override
- ▶ Diode Test
- ▶ Hfe Transistor Test
- ▶ Audible Continuity Test
- ▶ Data Hold & Range Hold
- ▶ Overload Protection
- ▶ Auto Power Off
- ▶ Power Source: 6F22(9V) X 1
- ▶ Fuse 200mA/250V
- ▶ IEC 1010-1 CAT II 600V
- ▶ Dimensions: 4.8" X 2.4" X 1.6"
- ▶ Weight: 5.3 oz.
- ▶ Accessories: Rubber Holster, Test Leads, Battery & Instruction Manual
- ▶ Blister Packed

Cat. No.	Description	Qty
57044	Multimeter	1
51056	Replacement Test Leads	1

Cat III Auto-Ranging Digital Multimeter with Temperature Probe



Santoprene is overmolded on the outer surface for comfort

- ▶ Conforms to international safety standard IEC61010-1 CAT III 600V
- ▶ Display: 1999 counts, digit is .63" high
- ▶ DC Voltage: 200m/2/20/200/600V±0.7%
- ▶ AC Voltage: 200m/2/20/200/600V±0.8%
- ▶ DC Current: 200μ / 2000μ / 20m / 200mA±1.2%, 2/10A ±2.0%
- ▶ AC Current: 200μ / 2000μ / 20m / 200mA ±1.5%, 2/10A ±3.0%
- ▶ DC Current: (with clamp, optional) :200/2000A (0.1mV/0.1A) ±1.2%
- ▶ AC Current: (with clamp, optional) :200/2000A (0.1mV/0.1A) ±1.5%
- ▶ Resistance: 200 / 2k/ 20k / 200k / 2M / 20MΩ ±1.2%,
- ▶ Temperature: 0° to 1800°F (-20° to 1000°C) ±3.0%
- ▶ Battery Test: 1.5V (test current approx 60mA)
- 3V (test current approx 30mA)
- 9V (test current approx 12mA)
- ▶ Auto range
- ▶ Data hold
- ▶ Continuity Test
- ▶ Diode Test
- ▶ Transistor hFE test
- ▶ Power: 1.5V (AAA) x 3
- ▶ Size: 6.2" X 2.9" X 1.2"
- ▶ Weight: 7.7oz.
- ▶ Secondary injection molded case
- ▶ Maximum value measurement
- ▶ Back light
- ▶ Auto Power off

Cat. No.	Inner Box Qty	Case Qty
57072	10	40