



Fig 1



Fig 2

- ▶ Toggle Switch
- ▶ Back & Side Wired
- ▶ Made of GE Lexan, Zinc Plated Steel Mounting Strap
- ▶ Accepts #12 or #14 Stranded or Solid Copper (Push-In #14 Solid Only)
- ▶ Washer Type Break Off Plaster Ears
- ▶ Large head Captive Combination Screws for quick wiring
- ▶ Easy-Access Green Hex-Head Ground Screw
- ▶ UL 94V-2 Flame Rating
- ▶ Temperature Rating: -40°F to 167°F



Fig 3



Fig 4

Amps	Voltage	Color	Residential Grade	Commercial Grade	Figure	Box Qty	Case Qty
<b>Single Pole</b>							
15	120/277	Ivory	82010		1	10	200
		White	82011		1	10	200
		Brown	82012		1	10	200
		Almond	82013		1	10	200
20	120/277	Ivory		82020	2	10	200
		White		82021	2	10	200
<b>Single Pole - No Mounting Ears</b>							
15	120	Black	82048		3	10	200
<b>Single Pole - (Lit When Switch is Off)</b>							
15	120/277	Clear	82045		4	10	200
<b>3-Way</b>							
15	120/277	Ivory	82030		1	10	200
		White	82031		1	10	200
		Brown	82032		1	10	200
		Almond	82033		1	10	200
20	120/277	Ivory		82025	2	10	200
		White		82026	2	10	200
<b>3-Way- (Lit When Switch is Off)</b>							
15	120/277	Clear	82046		4		
<b>4-Way</b>							
15	120/277	Ivory	82040		1	10	200
		White	82041		1	10	200

## Toggle Switches - Combinations



Fig 1



Fig 2



Fig 3

Amps	Voltage	Color	Residential Grade	Figure	Box Qty	Case Qty
<b>Single Pole - Double Switch</b>						
15	120	Ivory	82090	1	10	200
		White	82091	1	10	200
<b>Single Pole - Switch &amp; Receptacle</b>						
15	120	Ivory	82175	2	10	200
		White	82176	2	10	200
<b>Single Pole - Switch &amp; Pilot Light</b>						
15	120	Ivory	82095	3	10	200
		White	82096	3	10	200