

Tamper Resistant Duplex Receptacles



Residential



Commercial



Single

- ▶ 2 Pole 3 Wire
- ▶ Back & Side Wired
- ▶ Made of GE Lexan, Steel Mounting Strap
- ▶ Washer Type Break Off Plaster Ears
- ▶ Large Head Captive Tri-Combination Screws
- ▶ Built-in Protective Shutter Mechanism Designed to Prevent Insertion of Foreign Objects
- ▶ Clear Visible "TR" marking on Face
- ▶ Green Hex-Head Ground Screw
- ▶ UL 94V-2 Flame Rating
- ▶ Temperature Rating: -40°F to 167°F
- ▶ Accepts #12 or #14 Stranded or Solid CU (Push-In #14 Solid Only)

Amps	Voltage	Color	Residential Grade	Commercial Grade	Commercial Grade Single Receptacle	Box Qty	Case Qty
15 Amp 125V 5-15R							
15	125	Ivory	81950	82435	82510	10	200
		White	81951	82436	82511	10	200
		Almond	81953			10	200
20 Amp 125V 5-20R							
20	125	Ivory		82440	82455	10	200
		White		82441	82456	10	200
		Brown			82457	10	200

Tamper Resistant Isolated Ground Duplex Receptacles



- ▶ 2 Pole 3 Wire
- ▶ Back & Side Wired
- ▶ Made of GE Lexan
- ▶ Steel Mounting Strap
- ▶ 4 Corner Latches Secure Face
- ▶ Washer Type Break Off Plaster Ears
- ▶ Brass Strap Self Grounding Clip
- ▶ UL 94V-2 Flame Rating
- ▶ Temperature Rating: -40°F to 167°F
- ▶ Accepts #10 to #14 Stranded or Solid CU
- ▶ Touch Proof Side Barriers
- ▶ Large Head Captive Tri-Combo Screws

Amps	Voltage	Color	Isolated Ground	Box Qty	Case Qty
15 Amp 125V 5-15R					
15	125	Ivory	82445	10	200
		White	82446	10	200
		Orange	82449	10	200
20 Amp 125V 5-20R					
20	125	Ivory	82450	10	200
		White	82451	10	200
		Orange	82454	10	200

Tamper & Weather Resistant Duplex Receptacles



Complies with 2011 NEC Article 406.9 that states that all receptacles installed in wet & damp locations must be weather resistant. "WR" designations provide visual identification. Weather Resistant Receptacles offer protection from rain, snow, ice, moisture, & humidity when properly installed in an approved weather protective or while-in-use cover. Combine WR receptacles with any of our While-in-Use Covers.

- ▶ 2 Pole 3 Wire
- ▶ Back & Side Wired
- ▶ Made of GE Lexan, Steel Mounting Strap
- ▶ Washer Type Break Off Plaster Ears
- ▶ Large Head Captive Tri-Combination Screws
- ▶ Green Hex-Head Ground Screw
- ▶ UL 94V-2 Flame Rating
- ▶ Temperature Rating: -40°F to 167°F
- ▶ Accepts #12 or #14 Stranded or Solid CU (Push-In #14 Solid Only)

Amps	Voltage	Color	Commercial Grade	Box Qty	Case Qty
15 Amp 125V 5-15R					
15	125	Ivory	82500	10	200
		White	82501	10	200
		Brown	82502	10	200
20 Amp 125V 5-20R					
20	125	Ivory	82505	10	200
		White	82506	10	200
		Brown	82507	10	200