

CAT 6 (RJ-45) Unshielded Keystone Jacks



- ▶ CAT 6 components provide better insertion loss, return loss, & NEXT & FEXT characteristics, resulting in higher signal to loss ratios and a more reliable network
- ▶ Complies with TIA/EIA-568-C-2, ISO 1801 2nd Edition Class E, NEC Article 800
- ▶ 10 Gbps
- ▶ 250 MHz Bandwidth
- ▶ 110 Punchdown & Krone Type Termination
- ▶ 8 Conductor 22-26 AWG Solid & Stranded Wire
- ▶ 568A & 568B Wiring - Color Coded
- ▶ 50u Gold Plated Contacts
- ▶ Flammability Rating: UL94V-0

| Cat. No. | Color | Master Bag Qty |
|----------|------------|----------------|
| 88420 | Ivory | 10 |
| 88421 | White | 10 |
| 88422 | Blue | 10 |
| 88423 | Red | 10 |
| 88424 | Yellow | 10 |
| 88425 | Black | 10 |
| 88426 | Green | 10 |
| 88427 | Orange | 10 |
| 88428 | Lt. Almond | 10 |

CAT 6 (RJ-45) Unshielded Keystone Jacks - Rear Entry



- ▶ Same Features as Standard CAT6 Jacks listed above
- ▶ Conductor Termination at Rear of Jack

| Cat. No. | Color | Master Bag Qty |
|----------|-------|----------------|
| 88030 | Ivory | 10 |
| 88031 | White | 10 |

CAT 6 (RJ-45) Unshielded Keystone Jacks - Toolless



- ▶ Same Features as Standard CAT6 110 Punchdown Series Jacks listed above
- ▶ No Punch Down Tool Required

| Cat. No. | Color | Master Bag Qty |
|----------|-------|----------------|
| 88012 | Ivory | 10 |
| 88013 | White | 10 |

CAT 6 High Density Patch Panels



- ▶ Complies with TIA/EIA-568-C-2, ISO 1801 2nd Edition Class E, NEC Article 800
- ▶ Fits all Standard 19" Racks, Brackets & Cabinets
- ▶ 110 Punchdown & Krone Type Termination
- ▶ 10 Gbps, 250 MHz Bandwidth
- ▶ 12 Port Patch Panel includes 89D Mounting Bracket

| Cat. No. | Ports | Dimensions | Case Qty |
|----------|---------------------|------------------------|----------|
| 88442 | 12 Port Patch Panel | H2.25" X W19" X D1.32" | 25 |
| 88444 | 24 Port Patch Panel | H1.75" X W19" X D1.32" | 25 |
| 88446 | 48 Port Patch Panel | H3.50" X W19" X D1.32" | 5 |
| 88448 | 96 Port Patch Panel | H7.00" X W19" X D1.32" | 10 |

CAT 6 UTP Patch Cords



- ▶ CAT 6 patch cords provide better insertion loss, return loss, & NEXT & FEXT characteristics, resulting in higher signal to loss ratios and a more reliable network
- ▶ Complies with TIA/EIA-568-C-2, ISO 1801 2nd Edition Class E, NEC Article 800
- ▶ 10Gbps, 250 MHz Bandwidth
- ▶ 2-RJ45 Gold Plated 50u 8P8C Plugs
- ▶ 24AWG 4 Pair Stranded Wire
- ▶ Color: White

| Cat. No. | Length | Case Qty |
|----------|--------|----------|
| 88452 | 3' | 300 |
| 88454 | 5' | 200 |
| 88458 | 10' | 120 |
| 88460 | 14' | 100 |
| 88462 | 20' | 80 |