MORRIS	Temporary String Lighting	y indoor illum on jobsites, a	oor illumination commonly used on bsites, attics and garages up socket every 10Ft				
ting ression		<ul> <li>14/3 SJTW</li> <li>Accepts up to 150W lamps</li> <li>Non-Metallic Protective Cage Included</li> <li>OSHA &amp; NEC Compliant</li> </ul>					
E g		Cat. No.	Wire Guage/ Conductors	Length	Box Qty		
.9°%	to	71190 71191	14/3 14/3	50 FT 100 FT	1 1		
orary <sup>cords &amp; Sur</sup>	<ul> <li>Pigtail Socket</li> <li>Pigtail Type Medium Base Weatherproof Lampholder</li> <li>With Two #14, 6 inch Leads, One Black and One White</li> <li>Includes a rubber gasket that fits securely around the bulb neck to ensure water does not enter the socket</li> <li>Single Circuit, 660 Watt 250 Volt, Black, Right handed</li> </ul>						
<b>A</b> .5	Ru'	Cat. No.	Size	Box Qty	Case Qty		
<b>E</b> is		45260	#14 Stranded,6" I	Leads 25	250		
<b>Tem</b> Extensi	Victor Split Knob	<ul> <li>Used in Temporary Lighting Applications</li> <li>Glazed Porcelain</li> </ul>					
Y5	and the second sec	Cat. No.	Trac Size		Box Qty		
		18090 18091			100 50		
	3 Outlet Power Adaptor - w	► Unbreaka	any grounded ble Hard Rub Cat No. 89412			led outlets	
		► Converts	any grounded tivated Night Lig //1875W			ded outlets tically in the dark	
	6 Outlet Power Adaptor					֍֎	
			<ul> <li>Converts on 3-prong polarized outlet into 6 grounded outlets</li> <li>15A/125V/1875W</li> <li>UL 498A</li> </ul>				
			Cat. No.	Box Qty			
			89405	48			
	2 Prong To 3 Prong Adaptor Coverts any 2 Prong Polarized Outlet into a 3 Prong Grounded Outlet > 15A/125V/1875W > 2pcs/pack > UL 498A Rated						
			Cat. No. 89400	Box Qty 48			
			89400	48			