



GE
Lighting

35783 - Integrated 3ft LED Glass Tubes

LED11ET8/G/3/830

- ☞ Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall.
- ☞ Each LED tube is outfitted with an internal GE driver.
- ☞ The GE integrated LED tubes run on electronic T8 instant-start or programmed start ballasts.
- ☞ 66% longer life than LFL (50,000 vs. 30,000 hours)
- ☞ No UV
- ☞ Easy disposal, non-hazardous waste
- ☞ Check ballast compatibility at www.gelighting.com/LEDTUBES-ballast-compatibility
- ☞ UL Listed

Product Photo



GENERAL CHARACTERISTICS

Product Technology	LED
Rated Life (Hours)	50000 h
LED Tube Type	Glass
Environmental Rating	LED_Tube_Glass
10 Digit U	4316835783
Lamp Count	1
Life in Years	45.7 yr
Requested Structure	Sleeve
Estimated Energy Cost per Year	1.39
Bulb Shape	T8

PHOTOMETRIC CHARACTERISTICS

Rated Beam Spread	11 W
Initial Lumens-nominal	1400 lm
Color Temperature	3000 K

PRODUCT INFORMATION

Product Code	35783
Description	LED11ET8/G/3/830
Alternative Unit Of Measure	CASE
Standard Package Quantity	20
Ean UPC	043168357838
Standard Package GTIN	10043168357835
No Of Items Per Sales Unit	
No Of Items Per Standard Package	20
Sales Unit	Case
UCC	043168357838
Alternative Unit Of Measure	EACH
Standard Package Quantity	20
Ean UPC	043168357838
Standard Package GTIN	00043168357838
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
Sales Unit	Each
UCC	043168357838

DIMENSIONS

Bulb Max Overall Length-MOL	36.0 in
-----------------------------	---------

ELECTRICAL CHARACTERISTICS

Drive Current	45.7
Energy Efficiency Class	yr
Voltage <Nom>	120 V
Rated power (Watts)	11 W