

39275 - GE LED Plug-in

LED19GX24Q-V/835

- GE's LED plug-in lamps allow you to replace inefficient CFL 4 pin GX24q-3/GX24q-4 without tools or costly upgrades.
- Easily plugs into existing ballast
- Uses 50% less energy than CFL (18.5W LED vs. 42W CFL)
- These lamps are energy efficient, contain no lead or mercury, and meet the material restriction requirements of RoHS
- For example, using only 18.5 watts of energy, save over \$129 in energy costs over the rated life of a lamp versus a standard 42watt CFL lamp based on \$0.11 per kWh
- Advanced optics eliminate wasted light to deliver a more targeted beam with fewer lumens (1850 vs. 3200)
- Energy efficiency and long life mean fewer lamp replacements versus CFL light sources
- Check ballast compatibility at GELighting.com/LED4pincompatibility

Product Photo



GENERAL CHARACTERISTICS

GX24q

White

White

50000 h

4316839275

LED

No

1

45.7 yr

Carton

39275

CASE

6

6

Case

EACH

6

1

6

Each

6.42 in

LED19GX24Q-V/835

043168392754

043168392754

043168392754

043168392754

00043168392754

10043168392751

2.23

No

4-Pin Plug-in

Indoor Damp

Base Description Base Type Body Color Dimmable **Primary Application** Product Color Product Technology Rated Life (Hours) Dimmable / Non-Dimmable 10 Digit U Lamp Count Life in Years **Requested Structure** Estimated Energy Cost per Year

PHOTOMETRIC CHARACTERISTICS

Rated Beam Spread	18.5 W
Initial Lumens-nominal	1950 lm
Color Temperature	3500 K

PRODUCT INFORMATION

Product Code Description Alternative Unit Of Measure Standard Package Quantity Ean UPC Standard Package GTIN No Of Items Per Sales Unit No Of Items Per Standard Package Sales Unit UCC Alternative Unit Of Measure Standard Package Quantity Ean UPC Standard Package GTIN No Of Items Per Sales Unit No Of Items Per Standard Package Sales Unit UCC

DIMENSIONS

Bulb Max Overall Length-MOL

ELECTRICAL CHARACTERISTICS Drive Current 45.7

Energy Efficiency Class	yr
Voltage <nom></nom>	120 V
Rated power (Watts)	18.5 W

CAUTIONS & WARNINGS

Caution

Risk of Electric Shock

Suitable for damp locations

Direct replacement for CFQ42W /GX24q CFL lamps only

Not for use in totally enclosed or recessed luminaires

Not for use with dimmers

For use only with compatible ballasts. See list at: www.gelighting.com/LED4pin-compatibility