



I. Product Description

CRC® Roll-Up Door Lubricant is a superior lubricant that prevents friction and wear. Its unique viscosity allows it to cover more surface area and penetrate deep into the surface of all metal components found on roll-up and overhead doors. **CRC® Roll-Up Door Lubricant** displaces moisture and leaves a thin, long-lasting film to protect against rust and corrosion.

II. Applications

Recommended for use on all roll-up and overhead door assemblies including dock doors, trailer doors as well as side panel doors on beverage trucks. Use to lubricate and protect door hinges, pins, cables, chains, bearings, rollers, and tracks.

III. Features & Benefits

- **Ideal for use on all roll-up and overhead doors.**
- **Displaces Moisture.** Prevents corrosion and improves equipment life and performance.
- **Eliminates noise from squeaky rollers and hinges.**
- **360° Valve.** Product can be sprayed from any position -- even upside down.
- **M.S.D.[L.]™-Material Safety Data Label.** Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**

IV. Physical Properties without propellant

Flash Point	170°F TCC	Boiling Point	380°F (initial)
Odor	Pleasant	Solubility	Neg. in water
Appearance	Clear, blue-green liquid	VOC %	39.1%
Vapor Density	>air	Specific Gravity	0.8187
VOC Content (Fed)	320.1 g/L	Propellant	CO ₂
Sara Title III, Sect. 313 Chemicals	No		
Prop 65	No		

V. Specifications and Approvals

- NSF H2 Registered for use in meat and poultry plants.

VI. Performance Characteristics

Type of Film	Non-drying
Film Thickness	0.025 to 0.075 mils
ASTM D-877 (Dielectric Strength)	47,100 volts
ASTM D-56 (Flash Point)	170°F (TCC)
ASTM D-3233 (Falex Load Test)	1,500 lbs.
Corrosion Inhibitor	Indoor Only/up to 9 months Ferrous & Non-Ferrous Metals

VII. Directions

- Do not use on energized equipment.
- Spray rollers inside and out.
- Apply a smooth even coat to door tracks.
- Let stand for a few minutes then operate the door up and down the full length of the track.

VIII. Package Description

Part Number	Container Size
03029	16 oz Aerosol

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

X. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120°F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Industrial Products Division
Customer Service: (800)272-4620

Warminster, PA 18974
CRC On-Line: (215)442-6260