


PRODUCT DATA SHEET





Light activated fiberglass reinforced self adhesive repair

patch.

Applications

Repair of tanks, pipes, roofs, steps, switch boxes, radiators, mufflers, bumpers, boat bodies. Can be used on any wood, metal, glass, ceramic, concrete and plastic

surface.

Unit Package Description

6" x 9" Patch

Brand

CRC

Generic Description 1

Repair Patch

Net Fill

6" x 9"

078254140940

Unit Dimensions

UPC Code

6H x 9W

Units Per Case

12

Case Dimensions

12H x 6.38W x 7.5D in

Cases Per Pallet

96

Case Weight

10 lbs

I 2 of 5 Code

30078254140941

Appearance

Grey Sheet Lamination

Flash point (F)

840°F

Flash point (C)

449°C

riasir point (c)

Flammability Class - CPSC

447 0

Plastic Safe

None

Curing Time

Yes
5 Minutes (Sunny),50 Minutes (Cloudy)

curing time

9 kV/mm

Dielectric Strength

/ ICV/ !!!!!!

Working Temp (F)

-40 to 392°F

Working Temp (C)

-40 to 200°C

DOT Proper Shipping Name

Not Regulated

VOC % (Federal)

0.6

of CRC Industries, Inc.

VOC g/L (Federal)

Not Determined

Last revised: 5/4/2016

Page 1 of 2



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair



PRODUCT DATA SHEET



VOC Lbs./Gal. (Federal)
VOC Category

Not Determined Not Regulated

Last revised: 5/4/2016

Page 2 of 2



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com

