

Temporary Power

Temporary Industrial Lighting

Hazardous Location Lights

HUBBELL

Features

- Rated for use in Class 1, Div 1, Groups C & D locations & Class 2, Div 1, Groups F & G locations
- No plug included to allow flexibility for user
- Housing is made of corrosion resistant, lightweight, highly durable material.



Ordering Information

Description	UPC	Catalog Number
Fluorescent, Class 1, Div 1 Groups C & D, Class 2, Div 1 Groups F & G, 120V, less plug	783585467313	HBLXF50120V

Standards

UL
CSA
ETL

Specifications

Light Type	Fluorescent
Plug Type	No Plug
Length	23.5
Width	4

Performance

Electrical	
Lamp Life	14,000
Light Color	4100 K
Lumen Output	1800
Rating	120V
Wattage	26
Mechanical	
Cord Length	50 ft.
Cord Type	16/3 SOW
Environmental	
Explosion Proof	Class 1, Div 1 Groups C & D, Class 2, Div 1 Groups F & G

Online Resources

eCatalog

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

