

Kellems® Wire Management Products  
PolyTuff® Non-Metallic Liquidtight Fittings  
Liquidtight Fitting

# HUBBELL

## Features

- Nylon compression nut has a tapered dome to tighten ferrule onto conduit
- Neoprene O-ring provides liquidtight seal
- Non integral ferrule provides conduit seal and pullout protection

## Ordering Information

| Description                                      | Device Color | Trade Size  | UPC          | Catalog Number |
|--|--------------|-------------|--------------|----------------|
| Straight, Male Non-Metallic Liquidtight Fittings | Black        | 1 1/4" (35) | 783585333960 | P125NBK        |



## Online Resources

[eCatalog](#)  
[Installation Instructions](#)

## Listings

UL Listed  
CSA Certified

## Specifications

|              |          |
|--------------|----------|
| Material     | Nylon    |
| Sealing Ring | Neoprene |

## Performance

### Environmental

Flammability UL 94V-2  
Operating Temperature -30°F to +225°F (-34°C to +107°C)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

