

Low Voltage Programmable Thermostats



TH115-A-024T

Features

- 7 Day, 4 Settings Per Day
- Control Accuracy +/- 1°F of Setpoint Temp
- Pre-Programmed or Custom Settings
- Backlit Display, Energy Star Compliant

Standard Models

UPC#	MODEL	DESCRIPTION	LIST
686334			
523400	TH115-A-024T	Heat Only Temp Range:40-86°F Dims:4.89"H x 2.79"W x .91"D	121



TH147-P

Features

- 7 Day, 4 Settings Per Day
- Control Accuracy +/- 1°F of Setpoint Temp
- Pre-Programmed or Custom Settings
- Backlit Display, Energy Star Compliant

Standard Models

UPC#	MODEL	DESCRIPTION	LIST
686334			
523585	TH147-P	7 Day, 4 Settings per Day, Heating/Cooling, 1 Stage Heat/Cool Temp Range Heat:41-82°F, Cool:59-95°F Dims: 5"W x 3"H x 1"D,	144

2 Stage Low Voltage Thermostat

Features

- 24V single or 2 stage heat and cool
- Gas, oil, or electric with air conditioning.
- Heat only, Heat only with fan, Cool only.
- Battery only, common wire only or common wire with battery backup.
- System settings - Heat, Off, Cool, Auto, Emergency Heat.
- Temperature range - Heat 40-90°F, Cool 50-99°F.
- Dimensions: 3-9/16" H x 5-13/16" W x 1-1/2" D

Standard Models

UPC#	MODEL	VOLTAGE	TEMP RANGE	MAX AMP	LIST
686334					
691116	TW123 / TH5220D	750MV - 2DV	40-90 Heat 50-99 Cool	1.0	337



TW123

Round - Low Voltage

Features

- Heat only for 24V heating systems
- Does not contain Mercury
- White color
- Temperature range - 50° - 90°F
- Dimensions 3-11/16" diameter

Standard Models

UPC#	MODEL	DESCRIPTION	VOLTAGE	MAX AMP	LIST
686334					
260008	A6176	Heat/Cool	24 VAC	1.0	104

