

Portable Workstation Evaporative Coolers

40

Evap-Mini 500



FRONT
Patented

Evap-Mini 700



FRONT
Patented

PACKA77
FRONT



PACKA77
BACK (With Remote)

Evap-Mini - Features

- Lowers temperatures up to 30°F
- Water level sight tube and sump drain
- 3/4" garden hose connection for longer running
- Durable one-piece, rust free, leak-proof molded polyethylene housing
- Environmentally friendly efficient and effective resource use
- Cools for a fraction of the cost of air conditioning
- Cools without chemicals or refrigerants
- Long-term dependability-near maintenance-free operation
- Shipped completely assembled - ready to operate out of the box



PACKA77 - Features

- Lowers temperatures up to 30°F
- Low purchase cost and electricity usage
- Environmentally friendly (no refrigerant gas)
- Maximum portability; includes remote control
- Ideal for indoor / outdoor use

Standard Models

UPC#	MODEL	MOTOR HP	UNIT VOLTS	UNIT AMPS	CFM (2 Speed)		EFFECTIVE SQ. FT.	INTERNAL WATER (Gallons)	DIMENSIONS H x W x D (Inches)	WT. (LBS.)	LIST
					HIGH	LOW					
539777	EVAP-Mini 500	1/3	120	2.5	2000	1600	500	10	31" x 29" x 25"	72	1,280
539784	EVAP-Mini 700	1/3		5.6	3000	2400	700	16	38" x 29" x 25"	113	1,662
539791	PACKA77	----	120	2	----	----	600	8	44.3" x 17" x 22"	71	1,087

16" Portable Workstation Evaporative Cooler



FRONT
Patented

**15°F - 25°F OF EVAPORATIVE COOLING
- PLUS -
6°F - 8°F OF WIND CHILL COOLING**

EVAPORATIVE COOLING TEMPERATURE DROPS			
AIR TEMPERATURE	RELATIVE HUMIDITY		
	10%	30%	50%
80°	-22°	-16°	-10°
90°	-25°	-18°	-12°
100°	-29°	-21°	-14°
110°	-32°	-23°	-15°



BACK
Patented

42 Gallon internal water reservoir that allows the unit to operate approximately 8 hours without being connected to an external water source

PROVIDES COOLING UP TO A 900 SQ. FT. AREA

Features

- Durable polyethylene housing features leakproof, one piece construction
- Lowers temperatures 15-25°F depending on climate conditions
- Easy rolling poly on poly casters (EVAP16-3)
- Shipped completely assembled, ready to use
- Water level sight tube located on front of unit to indicate water level in tank
- Manufactured in USA



Standard Models

UPC#	MODEL	MOTOR HP	UNIT AMPS	CFM			EFFECTIVE SQ. FT.	INTERNAL WATER (Gallons)	DIMENSIONS L x W x H (Inches)	WT. (LBS.)	LIST
				HIGH	MED	LOW					
874809	EVAP16-3	1/2	4.6	3900	3500	2500	900	42	23 x 37.5 x 59	145	2,529