

Evap-Mini - Features

- Lowers temperatures up to 30°F
- Water level sight tube and sump drain
- ³/₄" garden hose connection for longer running
- Durable one-piece, rust free, leak-proof molded polyethylene housing
- Environmentally friendly efficient and effective
- Cools for a fraction of the cost of air conditioning
- Cools without chemicals or refrigerants
- Long-term dependability-near maintenance-free operation
- Shipped completely assembled ready to operate out of the box



Interte

Standard Models

MFG CATALOG NUMBER	MFG MODEL NUMBER	MOTOR HP	UNIT VOLTS	UNIT AMPS	CFM (2 Speed)		EFFECTIVE	INTERNAL	DIMENSIONS H x W x D	WT.
					HIGH	LOW	SQ. FT.	WATER (Gallons)	(Inches)	(LBS)
05397802	EVAP-Mini 700	1/3	120	5.6	3000	2400	700	16	38" x 29" x 25"	113

15°F - 25°F OF EVAPORATIVE COOLING - PLUS -6°F - 8°F OF WIND CHILL COOLING

01 01 01 WIND CHIEL COOLING								
EVAPORATIVE COOLING TEMPERATURE DROPS								
AIR	RELATIVE HUMIDITY							
TEMPERATURE	10%	30%	50%					
80°	-22°	-16°	-10°					
90°	-25°	-18°	-12°					
100°	-29°	-21°	-14°					
110°	-32°	-23°	-15°					

Hazardous Location - Standard Models



Hazardous Location - Specific Features

- All switches, motors, and cord connections are sealed to prevent sparking in combustible locations
- Shipped completely assembled, ready to use
- 120/240V operation
- Manufactured in U.S.A.
- Component Rating: Class 1A, Division D for Hazardous Location



CONTROL Patented



Hazardous Location - Standard Models

MFG CATALOG	MFG MODEL	MOTOR	UNIT	CFM			EFFECTIVE	INTERNAL	DIMENSIONS	WT.
NUMBER	NUMBER	- HV	AMPS	HIGH	MED	LOW	SQ. FT.	WATER (Gallons)	L x W x H (Inches)	(LBS)
08748302	EVAP36-HAZ	1/2	13.4		9600		2500	32	32 x 62 x 67	330
08748502	EVAP48-HAZ	1	18		20000		4000	40	36 x 74 x 86	460