Workstation Wall Mount Fan With Pivoting Arm

18" HIGH VELOCITY FAN MOUNTED ON 24", 40", or 60" PIVOTING ARMS



Mounting Arm Features

- 1-1/2" square, 14 gauge, steel tubing
- 3" x 5" x 3/16" mounting plate attaches with (4) 3/8" bolts
- 5' long., 18/3 SJTW conductor cord and NEMA 5-15 grounded plug
- Dual electrical outlets embedded in arm to allow connection of modular fan and optional light

Modular Fan Features

- 18" high velocity circulator, with 3 speed, 1/8 HP, 115V, 1-Phase permanently lubricated, totally enclosed, PSC motor
- Modular fan plugs into electrical outlet on arm

• Coated steel guards / Aluminum blades

• Meets OSHA standards / 1 year limited warranty

Use on loading docks to cool off workers entering workstations to cool off hot truck trailers.

Use at factory people or the machines.

Standard Models

UPC#	MODEL		ARM		FAN CFM		MAX	SHIPPING	LIST
686334			LENGTH	HIGH	MED	LOW	AMPS	WT (LBS)	LIST
800914	24-LDF-TE	18"	24"					31 lbs.	293
800921	40-LDF-TE	18"	40"	4600	4200	3200	2.2	38 lbs.	365
800938	60-LDF-TE	18"	60"					44 lbs.	392

Optional Modular Lights

Light Features

- Plugs into embedded outlet in arm
- On/Off switch and wire guard included
- Bulb included with DKL-QH and DKL-FL

Standard Models

UPC# 686334	MODEL	LIGHT HEAD TYPE	MAX WATTS	MAX LUMENS	AVE. BULB LIFE (HRS)	SHIPPING WT (LBS)	LIST
446563	DKL-INC	Incandescent	300	3,700	2,000	5 lbs.	74
446570	DKL-QH	Quartz Halogen	500	11,000	2,000	6 lbs.	111
484336	DKL-FL	Fluorescent	55	3,000	10,000	7 lbs.	129
470865	DKL-LED	LED	12	960	50,000	5 lbs.	412



Low Velocity "Navy Style" Workstation Fan

- 12" all metal, gray powder coated fan that can be wall, ceiling or bench mounted
- Direct wire electrical connection
- Toggle switch

- Fan head tilts 90° in horizontal and vertical plane
- Meets OSHA standards
- 1 year limited warranty

Designed to circulate air in confined spaces aboard US Navy ships Navy spec "MIL-F-68F"

Standard Models

Features





