

These circulators should be used in clean and dry commercial applications - such as schools, shops, offices or warehouses.

Commercial Circulator

Motor, blades, guards, and mount are packed and shipped in a single UPS-able carton.



- Pull chain switch.
- SJT type 3 conductor, 9' long cord.
- Coated steel guards with retaining clips.
- Steel hub/spider aluminum paddle blades.
- Pole adjusts center of fan from 43" to 60".
- Meets OSHA standards.
- 1 Year limited warranty.

Motor Specifications

• 120V

Features

- 1-Phase
- 1/4 HP

Ball bearingOpen ventilated

Standard Models

- 2-Speed
 - Permanently lubricated
 - Permanent split capacitor
- Permanent split

	UPC# 686334	MODEL	SIZE	MOUNT TYPE		CFM		WT.	LIST	
					HIGH	MED	LOW	AMPS HIGH	(LBS.)	LIST
	870627	CACU 24-P	24"	Pedestal Mount	5400	4900	4300	2.3	63	350
	870641	CACU 24-W	24"	Wall Mount	5400				43	299
	869744	CACU 30-P	30"	Pedestal Mount	6000	5500	4800	2.4	66	362
	870634	CACU 30-W		Wall Mount					46	310

Note: Stocked models may differ in appearance from photograph

TPI Commercial Oscillating Fans

Commercial wall mount and pedestal fans now available from TPI.

Standard Models

	RATING	UPC# 686334	MODEL	SIZE	HP	MOUNT TYPE	CFM		AMPS			RPM			WT.	LIST	
							HIGH	MED	LOW	HIGH	MED	LOW	HIGH	MED	LOW	(LBS.)	LIST
		874892	CACU 24-PO	24"	1/4	Pedestal Mount	7500	6060	4050	1.45	1.15	1.1	1100	1020	930	68	410
		874915	CACU 24-WO			Wall Mount										48	308
		874908	CACU 30-PO	30"	1/3	Pedestal Mount	8700	7500	6780	2.0	1.8	1.6	1100	1020	930	70	430
		874922	CACU 30-WO		1/3	Wall Mount										51	325

Note: Stocked models may differ in appearance from photograph