

# TPI Commercial Circulators



These circulators should be used in clean and dry commercial applications - such as schools, shops, offices or warehouses.

## Commercial Circulator

**Motor, blades, guards, and mount are packed and shipped in a single UPS-able carton.**

### Features

- Pull chain switch.
- SJT type 3 conductor, 9' long cord.
- Coated steel guards with retaining clips.
- Steel hub/spider aluminum paddle blades.
- Pole adjusts center of fan from 43" to 60".
- Meets OSHA standards.
- 1 Year limited warranty.



WALL MOUNT

### Motor Specifications

- 1-Phase
- 1/4 HP
- Ball bearing
- Open ventilated
- 120V
- 2 or 3-Speed
- Permanently lubricated
- Permanent split capacitor

### Standard Models

UPC# 686334	MODEL	SIZE	MOUNT TYPE	CFM			AMPS (HIGH)	WT. (LBS.)	LIST
				HIGH	MED	LOW			
870627	CACU 24-P	24"	Pedestal Mount	5400	4900	4300	2.3	63	350
870641	CACU 24-W		Wall Mount						
869744	CACU 30-P	30"	Pedestal Mount	6000	5500	4800	2.4	66	387
870634	CACU 30-W		Wall Mount						

Note: Stocked models may differ in appearance from photograph

# TPI Commercial Oscillating Fans

**Commercial wall mount and pedestal fans now available from TPI.**

### Standard Models

RATING	UPC# 686334	MODEL	SIZE	HP	MOUNT TYPE	CFM			AMPS			RPM			WT. (LBS.)	LIST
						HIGH	MED	LOW	HIGH	MED	LOW	HIGH	MED	LOW		
	874892	CACU 24-PO	24"	1/4	Pedestal Mount	7500	6060	4050	1.45	1.15	1.1	1100	1020	930	68	410
	874915	CACU 24-WO			Wall Mount											
	874908	CACU 30-PO	30"	1/3	Pedestal Mount	8700	7500	6780	2.0	1.8	1.6	1100	1020	930	70	430
	874922	CACU 30-WO			Wall Mount											

Note: Photograph is a representation of stocked models. Actual model may vary in appearance.