# Cabinet Exhaust Fans With Shutters

## Features

- 120V, 1-Phase or 230 / 460V, 3-Phase, ball bearing, permanently lubricated, drip proof motor - UL listed
- Permanently lubricated bearings on blade drive shaft
- Aluminum blade
- Aluminum shutter
- 20 gauge powder coated venturi
- 18 gauge galvanized steel housing
- 1725 RPM motot
- Motor frame size 56 / Shaft: 5/8”
- Ships fully assembled
- Meets OSHA Standards • 1 year warranty

## Standard Models

| SIZE | MOTOR | AMPS | | CFM | WT. (LBS) | 115V 1-PHASE | | | 230 / 460V 3-PHASE | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | HP | 115V | 230/460V | | | UPC# 686334 | MODEL | LIST | UPC# 686334 | MODEL | LIST |
| 24 | 1/3 | 5 | 1.9 / .9 | 3270 | 100 | 868396 | CBT-24B | 1514 | 868525 | CBT-24B-3 | 1609 |
| 30 | 1/3 | 6 | 1.9 / .9 | 7730 | 120 | 868402 | CBT-30B | 1704 | 868532 | CBT-30B-3 | 1829 |
| 36 | 1/2 | 8 | 2.3 / 1.1 | 9870 | 135 | 868419 | CBT-36B | 1924 | 868549 | CBT-36B-3 | 2082 |
| 42 | 3/4 | 11 | 3.3 / 1.5 | 14800 | 155 | 868426 | CBT-42B | 2366 | 868556 | CBT-42B-3 | 2554 |
| 48 | 1 | 15 | 3.8 / 1.9 | 21500 | 200 | 868518 | CBT-48B | 2933 | 868501 | CBT-48B-3 | 3123 |

## Dimensions

| SIZE | OUTSIDE DIMENSIONS | | | MAXIMUM REQUIRED INSIDE WALL OPENING |
|---|---|---|---|---|
| | HEIGHT | WIDTH | DEPTH | |
| 24” | 28 1/4” | 28 1/4” | 22 1/2” | 28 3/4” x 28 3/4” |
| 30” | 34 1/4” | 34 1/4” | 22 1/2” | 34 1/2” x 34 1/2” |
| 36” | 40 1/4” | 40 1/4” | 18 1/2” | 40 1/2” x 40 1/2” |
| 42” | 48 1/2” | 48 1/2” | 18 1/2” | 48 3/4” x 48 3/4” |
| 48” | 54 1/2” | 54 1/2” | 21 1/2” | 54 3/4” x 54 3/4” |