TW Series

Features

- Single and double pole models
- Wire leads
- Tamper resistant

Load Rating

- 22 Amps resistive @ 120 VAC
- 18 Amps resistive @ 277 VAC

UPC# 686334	MODEL	DESCRIPTION	TEMPERATURE SCALE	LIST
502009	TW145	SP, Beige with Leads	Tamper Resistant	59
502016	TW146	DP, Beige with Leads	Tamper Resistant	69
Master Carton: 25 Pcs, 12 lbs. (varies slightly by model), 16" x 14" x 5.5"				

Washdown Series

Features

- Single and double pole models
- Rain tight NEMA 4X rating
- Stainless steel hardware
- Coil capillary temperature sensor

UPC# 686334	MODEL	DESCRIPTION	TEMPERATURE SCALE	LIST
523424	TW155A	SP, Rain tight	40-110°F	179
523431	TW255A	DP, Rain tight	40-110°F	209
22 Amps @ 120/250/277 VAC, 5" x 5" x3" Case				

Industrial Series

Features

- Coil capillary (CKT) models
- Bi-Metal models (KT)
- Rugged steel case
- SPST & SDPT models
- Hard wired models rated for 22A resistive @125-250 VAC
- Corded models rated for 13A resistive @125VAC

UPC# 686334	MODEL	DESCRIPTION	RANGE	CONNECTIONS	SCALE	LIST
534048	CKTD110	SPDT Heat or Cool	40 - 110°F	Wire Leads	F	110
534086	KT110	SPST Heat Only	-10 - 100°F	Wire Leads	C & F	46
534109	KT121	SPST Heat Only	-10 - 100°F	6' Cord/Plug	C & F	51
534178	KTD110	SPDT Heat or Cool	-10 - 100°F	Wire Leads	C & F	47
534369	KTO110	SPST Cool Only	-10 - 100°F	Wire Leads	C & F	47
534215	KTO121	SPST Cool Only	-10 - 100°F	6' Cord/Plug	C & F	51
Master Carton: 13.75" x 14" x 9", Qty 9-12, 14lbs.-16lbs. depending on model						

L Series

Features

- 6' or 8' Capillary
- Rugged steel cage
- SPDT for Heat or Cool
- 25A resistive
- Rated differential of 6°F

UPC# 686334	MODEL	DESCRIPTION	RANGE	CAPILLARY	SCALE	LIST
534260	L06Y-01	SPDT Heat or Cool	0 - 90°F	6'	F	77
534277	L08Y-01	SPDT Heat or Cool	0 - 90°F	8'	F	90
Master Carton: 13.75" x 14" x 9", 12 Pcs, 18lbs.						