

Features

- Comes in sizes 36" & 42"
- Rocker switch
- SJT type 3 conductor, 12' long cord
- Aluminum, 3 paddle blade
- Spiral, wire front and rear guards
- Corrosion and dent proof high density polyethylene housing
- 8" wheels
- 36" & 42" swivel model rotates 360° in 12-1/2° increments and locks in place with a steel locking pin
- Meets OSHA standards
- 1 Year limited warranty

Motor Specifications

- 120V, 1-Phase
- 36"-1/3HP 42"-1/2HP
- Ball bearing
- Permanent split capacitor
- 2-Speed on 36" model
- 1-Speed on 42" model
- Permanently lubricated

Standard Models

UPC#	MODEL	FAN		MOTOR	CFM / RPM		AMPS	SHIPPING	LIST
686334	MODEL	SIZE	TYPE	HP	HIGH	LOW	(HIGH)	WT.(LBS.)	LIST
873048	PB 36-D	36"	STANDARD	1/3	12500 / 1040	9000 / 730	5.5	82	715
873055	PBS 36-D	36"	SWIVEL					110	974
873079	PB 42-D	42"	STANDARD	1/2	15 600	/ 1040	6.0	102	1006
873086	PBS 42-D	42"	SWIVEL	1/2	13,000			128	1235

Note: Photograph is a representation of stocked models. Actual model may vary slightly in appearance.

48" TPI Industrial Direct Drive Portable Blowers



Features

- Corrosion and dent proof high density polyethylene housing
- Rocker switch
- SJT type 3 conductor, 12' long cord
- Steel, 2 paddle blade
- Spiral, wire front and rear guards
- 10" wheels
- Swivel model rotates 360° in 12-1/2° increments and locks in place with a steel locking pin
- Meets OSHA standards
- 1 Year limited warranty

Motor Specifications

• 1-Phase

• 120V

• 3/4 HP

• 1-Speed

Ball bearing

- Permanently lubricated
- Permanent split capacitor

Features

UPC#	UPC# MODEL	SIZE	FAN TYPE	MOTOR	CFM	AMPS	DIMENSIONS			SHIPPING	LIST
686334 NODEL	SIZE	IMNTITE	HP	\ RPM	(HIGH)	"H"	"D"	"W"	WT.(LBS.)	1.131	
799782	PB 48-D-OP	48"	STANDARD	3/4	17,300 / 824	10.3	58.5	29	55.5	117	1454
799805	PBS 48-D-OP	48"	SWIVEL	3/4	17,300 / 824	10.3				142	1659

Note: Photograph is a representation of stocked models. Actual model may vary slightly in appearance.