Standard Product Models

UPC# 686334	MODEL	KW	BTU'S	VOLTS	PH	AMPS	CONTROL VOLTS	TEMP RISE °F	AIR THROW	CFM	RECOM'D MOUNTING HT.	WT. (LBS.)	LIST
644600	F1FUH03003	3.3	11200	208	1	15.9	208	26	26'	400	9'	36	693
644662	H1HUH03003			240	1	13.8	240						
644723	G1GUH03003			277	1	11.9	277						
711487	H3HUH03C03			240	3	7.9	240						
711494	F3FUH03C03			208	3	9.2	208						
711401	P3PUH03CA1			480	3	4	24						883
644617	F1FUH05003	5	17100	208	1	24.1	208	40	26'	400	9'	36	724
644679	H1HUH05003			240	1	20.8	240						
644730	G1GUH05003			277	1	18.1	277						
644938	F2FUH05C03			208	1 or 3	24.1 / 14.0	208					44	
644945	H2HUH05C03			240	1 or 3	20.8 / 12.1	240						
644884	P3PUH05CA1			480	3	6.1	24						958
718059	F1FUH07CA1	7.5	25600	208	1	36.1	24	42	36'	575	9'	40	1116
717373	H1HUH07CA1			240	1	31.3	24					41	
715188	G1GUH07CA1			277	1	27.1	24					41	
644792	F3FUH07C03			208	3	20.8	208					44	
644952	H2HUH07C03			240	1 or 3	31.3 / 18.1	240						
644891	P3PUH07CA1			480	3	9.1	24						1204
717090	F1FUH10CA1	10.0	34100	208	1	48.1	24	55	36'	575	9'	42	1230
680844	H1HUH10CA1			240	1	41.7	24						
717380	G1GUH10CA1			277	1	36.1	24						
644969	F2FUH10C03			208	1 or 3	48.1 / 27.8	208						
644976	HF2BUH10C03	10 / 7.5	34100	240	1 or 3	41.7 / 24.1	240	55				45	
			25600	208	1 or 3	36.1 / 20.8	208	42					
711425	P3PUH10CA1	10.0	34100	480	3	12.1	24	55				51	1275
644648	F1FUH12C03	12.5	42600	208	1	60.1	208	49	45'	800	10'	45	1980
644709	H1HUH12C03			240	1	52.1	240						
644815	F3FUH12C03			208	3	34.7	208						
644860	H3HUH12C03			240	3	30.1	240						
711432	P3PUH12CA1			480	3	15.1	24						2060
644655	F1FUH15CO3	15.0	51200	208	1	72.1	208	59	45'	800	10'	54	2179
644716	H1HUH15C03			240	1	62.5	240						
644822	F3FUH15C03			208	3	41.7	208						
644877	H3HUH15C03			240	3	36.1	240						
711449	P3PUH15CA1			480	3	18.1	24						2266
688307	F1FUH20CA1	20.0	68300	208	1	96.2	24	47	56'	1350	13'	55	2991
688420	H1HUH20CA1			240	1	83.3	24						
688314	F3FUH20CA1			208	3	55.6	24						
688437	H3HUH20CA1			240	3	48.2	24						
688321	P3PUH20CA1			480	3	24.1	24						
688444	F1FUH25CA1	25.0	85300	208	1	120.2	24	58	56'	1350	13'	55	3525
688338	H1HUH25CA1			240	1	104.2	24						
688451	F3FUH25CA1			208	3	69.5	24						
688345	H3HUH25CA1			240	3	60.2	24						
688468	P3PUH25CA1			480	3	30.1	24						
688475	H1HUH30CA1	30.0	102390	240	1	125	24	70	56'	1350	13'	60	4081
688369	F3FUH30CA1			208	3	83.4	24						
688482	H3HUH30CA1			240	3	72.3	24						
688376	P3PUH30CA1			480	3	36.1	24						
688406	P3PUH40CA1	40.0	136500	480	3	48.2	24	55	56'	2275	16'	75	5216
688789	P3PUH48CA1	48.0	163800	480	3	57.8	24	67	56'	2275	16'	78	6512

Factory & Field Installed Accessories

FACTORY INSTALLED OPTIONS		LIST
SUFFIX	DESCRIPTION	
F	Heat purge fan delay switch for 208 / 240 / 277V units (includes contactor & transformer)	201
	Heat purge fan delay switch for 480V units (contactor & transformer standard in unit)	117
S	Summer fan switch	58
CA1	24v Transformer (3.3 KW - 15 KW units) & Contactor	147
CA2	120v Transformer (3.3 KW - 15 KW units) & Contactor	
E	Epoxy Coating	111
T	SPST Thermostat	67
D	Disconnect Switch - 30 Amps	281
	Disconnect Switch - 40 Amps	322
	Disconnect Switch - 80 Amps	405
	Disconnect Switch - 100 Amps	411

FIELD INSTALLED ACCESSORIES			
UPC 686334	MODEL	DESCRIPTION	LIST
646239	DCS303	30 Amp Disconnect Kit	240
646246	DCS403	40 Amp Disconnect Kit	282
646253	DCS803	80 Amp Disconnect Kit	370
646260	DCS1003	100 Amp Disconnect Kit	373
687997	TUH1	25 Amp SPST Thermostat Kit	67
699105	UHB-1	wall / ceiling bracket - 3.3 KW - 15 KW units	90
699112	UHB-3	wall / ceiling bracket - 20 KW - 30 KW units	102
699129	UHB-4	wall / ceiling bracket - 35 KW - 48 KW units	129

NOTE: Factory installed heat purge fan delay option (F) requires unit to have CA1 or CA2 factory installed